

Previously known as: MICROGARD 2000 Ts PLUS - Model 111

Sealed seams provide additional protection in low hazard liquid spray applications..

DESIGN

MICROGARD® 2000 is designed to allow water vapour (perspiration) to escape from the suit yet will withstand saturation of liquid chemicals and filter 100% of particulates down to 0.01 microns in size*.

With serged and taped seams, MICROGARD® 2000 Ts PLUS provides an exceptional overall barrier to low hazard liquid spray and fine particulates.

* KAKEN Particle penetration test

SERGED AND TAPED SEAMS

Internal stitching which is overtaped to offer increased strength and an effective barrier to liquids and particulates.

SUIT FEATURES

- Hood
- Elasticated wrists, waist and ankles
- 2-way front zipper with resealable storm flap
- Finger loops
- Chin Strap

COLOURS

White

SIZES

S-5XL

Industries

- Life Sciences
- Automotive
- Metal fabrication
- Food Processing
- Chemical


Applications

- Product inspection
- Loading and hauling
- Fibre Glass/Resin Applications/Ceramic Fibres
- Body painting including surface inspection
- Cleaning of plant and machines
- Maintaining lab furniture and equipment


KEY FEATURES & BENEFITS

- Proven protective barrier to low concentration liquid chemicals, liquid & particulate biological hazards
- Comfortable to wear featuring moisture vapor permeable fabric (“breathable”) to help reduce the risk of heat stress
- Optimized body fit, improving wearer comfort and safety
- Anti-static, tested according to EN 1149-5
- Ultra Low Linting, reduced risk of contamination in critical areas
- Silicone free, critical in spray painting applications
- Tunnelled elasticated hood, wrists and ankles - Helps to minimize the risk of linting and cross contamination

Material Diagram



Seam Diagram



Performance Standards



Product Information

Product Information	
Available Sizes	XS, S, M, L, XL, 2XL, 3XL, 4XL, 5XL
Color	White
Product Material	Microporous polyethylene Laminate non-woven
Product Reference	2000 Ts PLUS - Model 134
Standards Overview	CE CATEGORY III (Type 4-B, Type 5-B, Type 6-B, EN 1073-2, EN 14126, DIN 32781, EN 1149-5)
Seam Type	Stitched and Taped

Suit components & accessories

Suit Components and Accessories

Design Features

Coverall, 3-piece hood, single zipper with re-sealable storm flap, thumb loops and chin strap. Elasticated waist, tunnelled elasticated wrists, hood and ankles.

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444

Australia

Ansell Limited
T: +61 1800 337 041

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

