

Gloves with sensitivity plus durability for all-around protection

- **Heightened sensitivity:** This lightweight glove is suitable for demanding jobs requiring tactile sensitivity and fine motor control
- **Tear resistance:** The high-quality nitrile formulation provides enhanced resistance against rips and tears
- **Genuine versatility:** Offers an unbeatable quality-to-price ratio for demanding jobs in a wide variety of industries



Industries

- Automotive
- Food Processing
- Janitorial / Sanitation

Recommended For

- Catering/Meal preparation
- Food processing and handling
- Meat, Fish and Food Processing
- Marinating
- Packing of fillets and ground meat
- Equipment, maintenance and repair
- Janitorial, clean up and maintenance
- Personal care and beauty salons

TECHNICAL DATA SHEET

Product Information	
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, ASTM D6319, EC 2023/2006, EC 2002/72, EN ISO 21420:2020, EN ISO 374-1:2016 Type C Chemical, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 13485, ISO 9001
Packaging Overview	100 gloves per dispenser/box 10 dispensers/box per carton/case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China
Product Segmentation	Standard Thin
Antistatic	No
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767, EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151-06 (2011), EN 374-2
Palm Thickness (mm/mils)	0.07/2.8		ASTM D3767, EN 420
Finger Thickness (mm/mils)	0.11/4.3		ASTM D3767, EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	14	14	ASTM D412 & D573
Elongation at Break (%)	500	400	ASTM D412
Force at break (N)	6	6	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	82134060	82134070	82134080	82134090	82134100

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

