NITRA-TOUCH™

Nitrile, powder-free personal protective equipment gloves with superior chemical protection

Non-sterile disposable gloves, ensuring reliable chemical resistance

- Specialized protection: Tested against over 100 chemicals and chemotherapy drugs*, Nitra-Touch™ gloves offer truly reliable hand protection
- Easy donning: The chlorinated internal surface treatment makes these gloves especially easy to don and remove
- Expanded protection: Their extended cuff ensures greater forearm and wrist protection, while offering a better fit over garments
- Improved grip: These nitrile disposable gloves also boast textured fingers, granting them better grip performance than standard disposable gloves
- Certified quality: They are compliant with EN 374 and EN 421 Personal Protective Equipment (PPE) standards, and possess EN ISO 374 Type B certification for chemical resistance



*see product packaging for details

Industries

Healthcare

Recommended For

- Tested against over 100 chemicals and chemotherapy drugs
- Extra protection over the wrist and arm
- Sustained, high-risk laboratory applications in healthcare settings
- Mortuary applications
- Protection from Type I latex allergy



TECHNICAL DATA SHEET

	Product Information		
External Glove Surface	Textured Fingers		
Audit Standards	ISO 9001		
Product Certification	Personal Protective Equipment Regulation (EU) 2016/425 Category III risks		
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case		
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.		
Country Of Origin	Thailand		
Antistatic	Not Tested		

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	300 / 11.8		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.13 / 5.1		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.14 / 5.5		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	N/A	N/A	ASTM D412 & D573
Elongation at Break (%)	≥500	≥400	ASTM D412
Force at break (N)	≥6	≥6	

Performance Standards and Regulatory Compliance













For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Technology



Ansell, $^{\textcircled{8}}$ and $^{\textcircled{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{9}}$ 2025 Ansell Limited. All Rights Reserved.

