

Electrical Insulating Gloves Class 0 -RIG014B

Ergonomically designed natural rubber insulating gloves for all-day safety and comfort

Previously known as: E016B







Durable, form-fitting electrical safety gloves, offering flexible, comfortable hand protection*

- Heightened flexibility and durability: ActivArmr[®]
 Electrical Insulating Gloves Class 0 RIG014B are
 made from natural rubber latex (through an eco conscious dipping process), for electrical safety
 gloves that are both durable and flexible
- Advanced ergonomics: These insulated rubber gloves' non-splayed fingers and hand-at-rest design minimize hand fatigue
- Elevated comfort: A spacious flared cuff ensures plentiful room for clothing and ventilation
- Specialized defenses: These electrical gloves are arc flash certified (APC 1 in combination with 96-002 leather gloves)*, can withstand a touch voltage AC maximum of 1000 V (DC maximum 1500) and tolerate acid, ozone and very low temperatures**
- Increased practicality: A smooth, case-hardened finish makes for easy donning and doffing
- Certified protection: As electrical PPE, they also comply with relevant CSA, NFPA and OSHA standards

*ATPV : 19 cal/cm $^{\text{M}}$ EBT : 47 cal/cm $^{\text{M}}$ with 96-002 leather gloves

**Category A, Z and C respectively



Industries

- Automotive
- Electrical
- Construction
- Mining
- Machinery and Equipment

Applications

- Applications with risk of touch voltage
- Electrical Contractors
- Hybrid engine manufacturing and repair
- Maintenance Repairs and Operations in all industrial environments (MRO)
- Mass Transit Repair and Maintenance
- Power maintenance, repair & transmission
- Telecom repair near electrical wires





Electrical Insulating Gloves Class 0 -RIG014B

Ergonomically designed natural rubber insulating gloves for all-day safety and comfort

Previously known as: E016B

Key Features

- Natural rubber latex formulation: Flexibility and durability ensured
- Ergonomic design: For hand protection with minimal fatigue
- Generous flared cuff: Ideal space for clothing and ventilation *Arc flash certified as per IEC 614821-2:2014 and ATSM F2675:2021 standards

Performance Standards & Regulatory Compliance



Specifications

BRAND STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
	Coating Material: Natural Latex Rubber Cuff Style: Straight Cuff with rolled beaded edge		7, 8, 8.5, 9, 9.5, 10, 10.5, 11, 12	360mm/14inch	Black	1 pair/pack, 10 pairs/carton

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region North America Region

Ansell Healthcare Europe NV Ansell Healthcare Europ Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. Blvd. Bernardo Quintana No. 7001-C, BIVO. Bernardo Quintana No. 70' Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

Ansell Healthcare Products LLC 111 Wood Avenue South, Suite 900 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Canada

Ansell Canada 105 Lauder Cowansville, QC J2K 2K8 Canada T: +1 800 363 8340

Ansell Limited Ansell Limited Level 3,678 Victoria Street, Richmond, Vic, 3121 Australia T: +61 1800 337 041 F: +61 1800 803 578

Asia Pacific Region

Ansell Global Trading Center Ansell Global Trading Center (Malaysia) Sdn Bhd Prima 6, Prima Avenue Block 3512, Jalan Teknokrat 6 T: +603 8310 6688 F: +603 8310 6699

Ansell, $^{@}$ and m are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{@}$ 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

