

85-303
Non-clean/Non-sterile CSM
RABS/Isolator Gloves

## Durable cleanroom isolator gloves, ensuring hard-wearing chemical resistance

Port size: 254mm/10" Thickness: 0.6mm/24 mil

- Specialized defenses: The AlphaTec® CSM Isolator Glove 85-303 is highly resistant to a wide range of concentrated acids and bases
- Elevated comfort: These CSM gloves are made from soft, flexible material, making them easy to use
- Prolonged glove life: The AlphaTec® CSM Isolator Glove 85-303 does not rapidly age, even with prolonged exposure to oxygen, UV rays and ozone
- Reduced contamination risks: As these safety gloves are white in color, contamination is easier to detect

#### **KEY FEATURES & BENEFITS**

- Hard-wearing CSM composition: Protects from concentrated acids/bases
- Flexible material: For heightened ease of use and comfort
- **Durable design:** Good resistance against oxygen, UV rays and ozone







# **85-303**Non-clean/Non-sterile CSM RABS/Isolator Gloves

### **TECHNICAL DATA SHEET**

Product Reference	85-303
Material	Chlorosulfonated polyethylene_CSM
Color	White
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 120°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-1:2016 Type B, EN ISO 374-5:2016, Category III, UKCA





## **85-303**Non-clean/Non-sterile CSM RABS/Isolator Gloves

#### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	800 / 32	EN ISO 21420
Port Size	254mm/10"	
Target Single Wall Palm Thickness (mm/mil)	0.6 / 24	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.6 / 24	EN 455-2

### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level	
Abrasion Resistance	Level 3	
Blade Cut Resistance	Level 1	
Tear Resistance	Level O	
Puncture Resistance	Level 1	
ISO 13997 Cut Resistance	Level A	

#### **ORDERING INFORMATION**

	PORT SIZE	10"/254mm	10"/254mm
	SIZE	9.5	11
85-303	REORDER NO.	85303095	85303110

**Performance Standards and Regulatory Compliance** 

**C €** 0493







## For additional information visit us at www.ansell.com, or call us at

**Europe, Middle East & Africa Region** Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

#### UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890



Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking <sup>®</sup> 2025 Ansell Limited. All Rights Reserved.

