

85-504 Non-clean/Non-sterile EPDM RABS/Isolator Gloves

EPDM RABS/isolator gloves, developed with premium FDA-approved material, for reduced glove changes

Port size: 305mm/12" Thickness: 0.4mm/16 mil

- Optimized durability: The AlphaTec® EPDM Isolator Glove 85-504 is ideal for repeated autoclave sterilization (up to 50 times), meaning fewer replacements over a sustained period
- Assured protection: These EN ISO 374compliant RABS gloves deliver high resistance to hydrogen peroxide and common disinfecting chemicals
- Improved eco-friendliness: The AlphaTec® EPDM Isolator Glove 85-504 model is also halogen-free, making it suitable for disposal by incineration
- Food handling compliance: This model of isolator glove also complies with FDA Food Contact regulation 21 CFR177 (FDA Positive List) for Indirect Food Additives

KEY FEATURES & BENEFITS

- **EPDM material**: Perfect for repeated autoclave sterilization
- Chemical resistance: Hydrogen peroxide/common disinfecting chemicals
- FDA food handling compliance: Safe and suitable for food handling







85-504 Non-clean/Non-sterile I

Non-clean/Non-sterile EPDM RABS/Isolator Gloves

TECHNICAL DATA SHEET

Product Reference	85-504
Material	Ethylene propylene diene rubber_EPDM
Color	Black
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 130°C
Cleanroom Class	Non-Critical Environment
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016, EN ISO 21420:2020, EN ISO 374-1:2016 Type B, EN ISO 374-5:2016, Category III, UKCA





85-504Non-clean/Non-sterile EPDM RABS/Isolator Gloves

PHYSICAL PROPERTIES

	Typical Values	Testing Method
Typical Length (mm/in)	800/32	EN ISO 21420
Port Size	305mm/12"	
Target Single Wall Palm Thickness (mm/mil)	0.40 / 16	EN 455-2
Target Single Wall Finger Thickness (mm/mil)	0.40 / 16	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.40 / 16	EN 455-2

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level	
Abrasion Resistance	Level 2	
Blade Cut Resistance	Level 1	
Tear Resistance	Level 1	
Puncture Resistance	Level 1	
ISO 13997 Cut Resistance	Level A	

ORDERING INFORMATION

	PORT SIZE	12"/305mm	12"/305mm
	SIZE	9.5	11
85-504	REORDER NO.	85504095	85504110

Performance Standards and Regulatory Compliance

C € 0493







For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133 Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890





