

85-503
Non-clean/Non-sterile EPDM
RABS/Isolator Gloves

# EPDM RABS/isolator gloves, manufactured with premium FDA-approved material, for fewer glove changes

Port size: 254mm/10" Thickness: 0.6mm/24 mil

- Optimized durability: The AlphaTec® EPDM Isolator Glove 85-503 is designed for repeated autoclave sterilization (up to 50 times), resulting in fewer replacements
- Assured protection: These isolator gloves satisfy EN ISO 374 chemical resistance standards, for assured protection from hydrogen peroxide and common disinfecting chemicals
- Increased eco-friendliness: The AlphaTec® EPDM Isolator Glove 85-503 is halogen-free, making it safe for disposal by incineration
- Food handling compliance: These EPDM gloves adhere to FDA Food Contact regulation 21 CFR 177 (FDA Positive List) for Indirect Food Additives

### **KEY FEATURES & BENEFITS**

- EPDM composition: Suitable for repeated autoclave sterilization
- Chemical resistance: Hydrogen peroxide/common disinfecting chemicals
- FDA food handling compliance: For safe, dependable isolator gloves







## **85-503**Non-clean/Non-sterile EPDM RABS/Isolator Gloves

### **TECHNICAL DATA SHEET**

Product Reference	85-503
Material	Ethylene propylene diene rubber_EPDM
Color	Black
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 130°C
Cleanroom Class	Non-Critical Environment
Shelf Life	Three (3) years from date of manufacture.
Tested For Use With Chemotherapy Drugs	No
Standards	CE 0493, EN 388:2016, EN ISO 21420:2020, EN ISO 374-1:2016 Type B, EN ISO 374-5:2016, Category III, UKCA





### **85-503**Non-clean/Non-sterile EPDM RABS/Isolator Gloves

### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	800/32	EN ISO 21420
Port Size	254mm/10"	
Target Single Wall Palm Thickness (mm/mil)	0.60 / 24	EN 455-2
Target Single Wall Finger Thickness (mm/mil)	0.60 / 24	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.60 / 24	EN 455-2

### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level	
Abrasion Resistance	Level 2	
Blade Cut Resistance	Level 1	
Tear Resistance	Level 1	
Puncture Resistance	Level 1	
ISO 13997 Cut Resistance	Level A	

### **ORDERING INFORMATION**

	PORT SIZE	10"/254mm	10"/254mm
	SIZE	9.5	11
85-503	REORDER NO.	85503095	85503110

Performance Standards and Regulatory Compliance

**C €** 0493







### For additional information visit us at www.ansell.com, or call us at

**Europe, Middle East & Africa Region** Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

### North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

### UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890



Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking <sup>®</sup> 2025 Ansell Limited. All Rights Reserved.

