

**GSL20NITPP26** Validated Sterile Nitrile RABS / Isolator Sleeve

# Validated sterile nitrile RABS/isolator sleeves with low particle levels and superb ESD properties

- Assured quality: The BioClean<sup>™</sup> Sterile Nitrile RABS/Isolator Sleeve GSL20NITPP26 is 100% visually inspected and triple bagged to ensure high-quality protection
- Increased versatility: These isolator sleeves are compatible with autoclaving, VHP and IPA, enabling the use of three sterilization methods
- Improved practicality: In addition, the BioClean<sup>™</sup> Sterile Nitrile RABS/Isolator Sleeve GSL20NITPP26 are compatible with a broad range of cuff systems
- Enhanced features: They also have extremely low particulate levels and excellent ESD properties

## **KEY FEATURES & BENEFITS**

- Triple bagged and 100% visually inspected: High-quality arm protection
- Versatile RABS/Isolator sleeves: Compatible with a variety of cuff systems
- Autoclave compatibility: Withstands pressurized, high-temperature conditions

#### Industries

- Pharmaceutical Manufacturing
- Laboratory Research and
  Development
- Raw Material and Preparation
- Biotechnology Manufacturing
- Sterile Processing Department
- Semiconductor manufacturing



Ansell





## **TECHNICAL DATA SHEET**

Product Reference	GSL20NITPP26
Material	Nitrile
Color	White
External Glove Surface	Smooth
Cuff Style	Beaded
Audit Standards	ISO 14001, ISO 9001:2008, NEBB Certified Cleanrooms
Packaging Overview	One piece per sealed inner PE bag; one inner bag per sealed second inner PE bag; one second inner bag per sealed outer PE bag; 20 outer bags per lined inner white Correx polyethylene box (20 pieces).
Storage Instructions	Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.
Country Of Origin	Malaysia
Temperature Range	From -10°C to 120°C
Sterilization Method	GAMMA irradiation (25 kGy)
Cleanroom Class	Class 10/ISO 4 & EU GMP Grade A
Shelf Life	Three (3) years from date of manufacture.
Protein Level	N/A: contains no natural rubber latex
Antistatic	Yes
Standards	Category III, CE 0493, EC 1935/2004, ISO 11137-1:2006, EN 388:2016 +A1:2018, EN 420:2003 + A1:2009, EN 455 Part 2, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 421:2010





### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	660/26	EN ISO 21420
Port Size	8"	
Target Single Wall Cuff Thickness (mm/mil)	0.50/20	EN 455-2

#### **ORDERING INFORMATION**

	PORT SIZE	8"/203mm
	SIZE	8"/203mm
GSL20NITPP26	REORDER NO.	GSL20NITPP26

#### Technology



## Performance Standards and Regulatory Compliance





#### For additional information visit us at www.ansell.com, or call us at

**Europe, Middle East & Africa Region** Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

**Asia Pacific Region** Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region Ansell Healthcare Products LLC US T: +1 800 800 0445 US F: +1 800 800 0445 CA T: +1-800-363-8340

\_C Anse T: +6

CA T: +1.800.800.0445 CA T: +1.800-363-8340 Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133 Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Ansell, <sup>®</sup> and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

