

## Black nitrile exam gloves, delivering reliable extended protection with secure grip

- **Dark black color:** Dirt-masking black color makes potential hazards easier to spot
- **Extended protection:** A longer cuff offers expanded protection of the forearm and wrist
- **Elevated comfort and grip:** The soft, flexible nitrile composition provides comfort while the textured design ensures a confident grip
- **NFPA approved:** Compliance with NFPA 1999 Emergency Medical Glove Requirements makes them a suitable choice for US first responders



### Industries

- Automotive
- Automotive Aftermarket
- Chemical
- Correctional Facilities
- Emergency Medical Services
- Healthcare
- Law Enforcement
- Life Sciences
- Machinery and Equipment
- Manufacturing
- Recycling and Waste Disposal
- Transportation

### Recommended For

- Administering drugs
- Equipment, maintenance and repair
- Extra protection over the wrist and arm
- Standard patient examinations
- Overdose situations
- Emergency services
- Inspection of parts, equipment
- Laboratory analysis
- Paint shop
- Positioning patients
- Raw material sample collection
- Oil, fluids and filter change
- General Purpose Auto Aftermarket

# TECHNICAL DATA SHEET

Product Information	
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Thailand
Product Segmentation	High Risk
Antistatic	Yes EN1149

## PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	300 / 12		ASTM D3767, EN 420
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151, EN 374-2
Palm Thickness (mm/mils)	0.15 / 5.9		ASTM D3767, EN 420
Finger Thickness (mm/mils)	0.17 / 6.7		ASTM D3767, EN 420
	<b>BEFORE AGING</b>	<b>AFTER AGING</b>	
Ultimate Tensile Strength (MPa)	14	14	ASTM D412 & D573
Elongation at Break (%)	500	500	ASTM D412
Force at break (N)	6	6	EN 455-2

## ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	93862070	93862080	93862090	93862100	93862110

## Performance Standards and Regulatory Compliance



## For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

### Asia Pacific Region

MY +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

### North America Region

Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

### Latin America & Caribbean Region

BR +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

### Russia

Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

