

### 55-100 Non-clean/Non-sterile Latex (NRL)

**RABS/Isolator Gloves** 

# NRL RABS/Isolator gloves, offering personal protection with heightened tear and abrasion resistance

Port size: 152mm/6"
Thickness: 0.51mm/20 mil

- Sustained protection: AlphaTec® NRL RABS and Isolator Gloves 55-100 boast EN388:2016 Level 2 tear and abrasion resistance
- Improved dexterity: Medium-level thickness means these isolator gloves offer hand protection with added dexterity, facilitating daily use
- Limited contamination risks: Unlined and translucent, these RABS gloves are easy to clean and present fewer contamination risks

#### **KEY FEATURES & BENEFITS**

- EN388:2016 compliance: Heightened tear and abrasion resistance
- Medium thickness: Enhanced dexterity, for easier parts handling
- Unlined: Contamination risks minimized, cleaning made easy







# 55-100

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

#### **TECHNICAL DATA SHEET**

Product Reference	55-100		
Material	Natural Rubber Latex		
Color	Natural		
Shape	Ambidextrous		
External Glove Surface	Smooth		
Cuff Style	Beaded		
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.		
Available Sizes	8, 9, 10		
Temperature Range	From -30°C to 50°C		
Shelf Life	Three (3) years from date of manufacture.		
Standards	CE 0493, EN388:2016, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN ISO 374-5:2016, Category III, UKCA		





## 55-100

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

#### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	711 / 28	EN 455-2
Port Size	152mm/6"	
Target Single Wall Palm Thickness (mm/mil)	0.51 / 20	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.51 / 20	EN 455-2

#### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level		
Abrasion Resistance	Level 2		
Blade Cut Resistance	Level O		
Tear Resistance	Level 2		
Puncture Resistance	Level O		
ISO 13997 Cut Resistance	Level A		

#### **ORDERING INFORMATION**

	PORT SIZE	6"/152mm	6"/152mm	6-8" / 152-203mm
	SIZE	8	9	10
55-100	REORDER NO.	55100080	55100090	55100100

#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

#### **Asia Pacific Region**

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

#### UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890 Performance Standards and Regulatory Compliance

**C** € 0493









Ansell,  $^{\textcircled{8}}$  and  $^{\textcircled{m}}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\textcircled{c}}$  2025 Ansell Limited. All Rights Reserved.

