

66-670 Jacket

NFPA 1990 (NFPA 1992) and NFPA 2112 certified jacket is breathable, re-usable and resistant to chemical splash, flash fire, arc flash and hot liquids.

NFPA 1990 (NFPA 1992) and NFPA 2112 certified jacket, combining outstanding comfort and durability with liquid chemical splash, flash fire, hot liquids and arc resistance..

AlphaTec® 6667x series coverall is made of a Nomex® based fabric containing a breathable membrane.

It offers flash fire protection as well as exceptional liquid chemical splash protection, while also helping to manage heat stress by allowing body heat to disperse through the fabric. The worker is protected and comfortable throughout a full shift.

Design features include:

- Raglan sleeves, designed for comfortable arm movement
- Adjustable hook and loop closure straps at the wrist, ankle and front flap for a snug fit
- Double front zipper flap for secured closure
- Heavy duty zipper
- Front tab to clip a microphone or other devices
- Optional detachable hood (66-664) which is attached to the collar by means of a Velcro hook and loop



Industries

- Chemical
- Food Processing
- Mining
- Maintenance
- Metal fabrication


Applications

- Plant disinfection and sanitization
- Chemical Handling
- Rescue Operations
- Rescue extraction from confined spaces
- Oil Platforms
- Mining
- Metal Plating
- Food Processing
- Sanitation
- Utilities
- Energy
- Water plants
- Pulp and Paper Production
- Transport of hazardous substances
- Potential Flash Fire

KEY FEATURES & BENEFITS

- Chemical splash fabric provides protection with penetration data for more than 70 chemicals
- FR fabric resists flash fire, arc flash and hot liquids
- Breathable fabric maximizes comfort, reducing the risk of heat stress and increasing productivity
- Sealed seams and double front storm flap ensure the whole garment offers leak-tight protection from chemical spray
- FR heavy duty zipper
- Hook-and-loop fastenings at cuffs
- Durable laminated fabric system is machine washable for longer, cost-effective service life
- Certified according to NFPA 1990 (NFPA 1992)
- Certified according to NFPA 2112 - 2018 - Standard on Flame-Resistant Clothing for Protection of Industrial Personnel Against Short-Duration Thermal Exposures from Fire

Seam Diagram



Performance Standards



ASTM F1671



EN 1149-5

Product Information

| Product Information | |
|---------------------|---|
| Available Sizes | S, M, L, XL, 2XL, 3XL, 4XL, 5XL |
| Color | Blue |
| Country Of Origin | Canada |
| Packaging Overview | Individually Packed |
| Product Material | White Nomex [®] inner with breathable membrane and Blue Nomex [®] outer |
| Product Reference | 66-670 Jacket |
| Standards Overview | <ul style="list-style-type: none">• NFPA 1990 (NFPA 1992)• NFPA 2112• Tested to ASTM F955-2015 - Standard Test Method for Evaluating Heat Transfer through Materials for Protective Clothing Upon Contact with Molten Substances• ASTM F1671 - Resistance to bloodborne pathogens• EN 1149-5 - Electrostatic properties |
| Seam Type | Stitched and Taped |
| Shelf Life | 5 years |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444

Australia

Ansell Limited
T: +61 1800 337 041

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

