

Black nitrile exam gloves, delivering reliable extended protection with secure grip

- **Extended protection:** A longer cuff offers expanded protection of the forearm and wrist
- **Dark black color:** Dirt-masking black color makes potential hazards easier to spot
- **Elevated comfort and grip:** The soft, flexible nitrile composition provides comfort while the textured design ensures a confident grip
- **Certified performance:** These gloves meet National Fire Protection Association 1950 Emergency Medical Glove Requirements, indicating they are approved for use by first responders in the US



Industries

- Automotive
- Automotive Aftermarket
- Correctional Facilities
- Emergency Medical Services
- Fire and Rescue
- Life Sciences
- Chemical
- Manufacturing
- Recycling and Waste Disposal
- Transportation

Recommended For

- General Purpose Auto Aftermarket
- Raw material sample collection
- Overdose situations
- Laboratory analysis
- Paint shop
- Positioning patients
- Oil, fluids and filter change
- Administering drugs
- Equipment repair and maintenance
- Extra protection over the wrist and arm
- Standard patient examinations
- Emergency services
- Inspection of parts, equipment

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, ASTM D6319, CE 0493, EC 1935/2004, EC 2002/72, EC 2023/2006, EN 455 1-4, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, EN 421:2010 Radioactive Contamination, FDA21 CFR 177-2600-US Food Contact Approved, NFPA 1999:2018, ISO 9001, ISO 10993-10, ISO 10993-23, ISO 13485, ISO 18889:2019, UKCA, EU Food Contact Approved
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Thailand
Product Segmentation	High Risk
Antistatic	Yes EN1149
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	300 / 12		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 374-2
Palm Thickness (mm/mils)	0.15/5.9		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.17/6.7		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	500	500	ASTM D412
Force at break (N)	6	6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	93862070	93862080	93862090	93862100	93862110

Performance Standards and Regulatory Compliance

CE 0493

MD



EN ISO 374-1:2016
Type B



J K P T

EN ISO 374-5



VIRUS

EN 421



ISO 9001



ISO 10993-10



ISO 10993-23



ISO 13485



ISO 18889



G1

UK

CA

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Russia
Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

