

# 69-318

Lightweight Latex Exam Glove with Enhanced Tactility

# Lightweight latex gloves that provide superior comfort and tactility

- Exceptional fit and feel: Made from high-quality elastic latex, TouchNTuff<sup>®</sup> 69-318 gloves offer superior comfort
- Heightened sensitivity: The thin design provides excellent tactility when compared to standard latex gloves
- Secure handling: Textured fingers for easy handling of small objects and delicate instruments
- Food handling compliance: These gloves are food-handling compliant, and thus are suitable for a wide variety of food handling applications

CAUTION: This product contains natural rubber latex, which may cause allergic reactions



#### **Industries**

- Life Sciences
- Food Processing
- Chemical

# **Recommended For**

- Sample taking and processing
- Testing
- Vehicle maintenance
- Food contact
- All food processing, applications that have food contact
- Food processing and handling
- Meat, Fish and Food Processing
- Secondary food processing



# **TECHNICAL DATA SHEET**

	Product Information
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	Category III, EN ISO 21420:2020, EN ISO 374-1:2016 Type B KPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 13485, ISO 9001, UKCA
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
<b>Product Segmentation</b>	Multi-Purpose
Antistatic	Not Tested
Silicone Free	Yes

### **PHYSICAL PROPERTIES**

	Typical Values		Testing Method
Length (mm/inches)	th (mm/inches) 240 / 9.5		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	om from Holes (Inspection level I) 1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.14 / 5.5		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 650	≥ 500	ASTM D412

#### **ORDERING INFORMATION**

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	6931800S	6931800M	6931800L	693180XL

#### **Performance Standards and Regulatory Compliance**













# For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell. CO: +57 1 288 3247 latam.medical@ansell.

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell,  $^{\textcircled{8}}$  and  $^{\textcircled{M}}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\textcircled{9}}$  2025 Ansell Limited. All Rights Reserved.



