

An unparalleled combination of chemical splash protection, comfort and durability

- **World leader:** TouchNTuff® 92-600 gloves are the world's leading disposable gloves for chemical splash protection
- **Superior protection:** Made with TNT™ Chemical Splash Resistance Technology, these gloves effectively safeguard hands from exposure to harmful chemicals
- **Elevated comfort:** Super soft nitrile provides a comfortable feel during extended wear
- **Robust durability:** EN388 certified, meeting level 1 abrasion to prevent ripping and tearing during heavy-duty work
- **Prevents surface defects:** Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes



Industries

- Life Sciences
- Food Processing
- Automotive
- Machinery and Equipment
- Chemical
- Agriculture
- Utilities
- Warehousing

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory analysis
- Chemical Handling

TECHNICAL DATA SHEET

Product Information	
External Glove Surface	Smooth
Audit Standards	ISO 9001
Packaging Overview	XS-XL: 100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case XXL: 90 gloves per dispenser, 10 dispensers per case, 900 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia, Sri Lanka, Thailand
Product Segmentation	Robust
Antistatic	Yes EN1149
Silicone Free	Yes

PHYSICAL PROPERTIES

	Typical Values	Testing Method	
Length (mm/inches)	240 / 9.5	ASTM D3767, EN 420	
Freedom from Holes (Inspection level I)	4.0 AQL (North & South America, except Brazil) / 1.5 AQL (Europe, Middle East, Africa, Asia, Pacific, Brazil)	ASTM D5151, EN 455-1	
Palm Thickness (mm/mils)	0.125 / 4.9	ASTM D3767, EN 420	
Finger Thickness (mm/mils)	0.14 / 5.5	ASTM D3767, EN 420	
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 24	≥ 25	ASTM D412 & D573
Elongation at Break (%)	≥ 600	≥ 525	ASTM D412
Force at break (N)	≥ 10	≥ 10	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	92600060	585834	585835	585836	585837	92600110

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

