

Durable disposable gloves for extended wear time

- **Durability:** Robust design allows for longer wear time in a variety of heavy-duty jobs
- **Secure grip:** Fully textured for a firm, safe grip in dry and wet environments
- **Genuine versatility:** Designed for heavy-duty jobs across industries, and available in a broad range of sizes through online retailers
- **Cost-effective:** Durable protection offered at excellent value
- **Food handling compliance:** Suitable for a wide range of food handling applications, as per GB 4806.11 (contact time with foodstuffs at 40°C/104°F, for a maximum of 30 minutes)



Industries

- Agriculture
- Food Processing
- Janitorial / Sanitation

Recommended For

- Equipment, maintenance and repair
- Fastening, screwing, unscrewing parts
- Food processing and handling
- Handling of machined parts coated with light oil
- Lab work, blending, compounding, filling, cleaning
- Maintenance and equipment clean up
- Mechanical jobs
- Handling of paint/glue guns and sprayers

TECHNICAL DATA SHEET

| Product Information | |
|------------------------|--|
| External Glove Surface | Fully Textured |
| Audit Standards | ISO 13485, ISO 9001 |
| Product Certification | Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks |
| Packaging Overview | 500 gloves per dispenser, 50 dispensers per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Product Segmentation | Robust |
| Antistatic | No |
| Silicone Free | Yes |

PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|---|---------------------|--------------------|---------------------|
| Length (mm/inches) | 240 / 9.5 | | ASTM D3767,EN 420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151,EN 374-2 |
| Palm Thickness (mm/mils) | 0.17 / 6.7 | | ASTM D3767,EN 420 |
| Finger Thickness (mm/mils) | 0.19 / 7.5 | | ASTM D3767,EN 420 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | 16 | 16 | ASTM D412-06a |
| Elongation at Break (%) | 500 | 400 | ASTM D412-06a |
| Force at break (N) | 8 | 8 | EN 455-2 |

ORDERING INFORMATION

| Size | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) |
|--------------|-------------|-------------|-------------|
| Product Code | 10135070 | 10135080 | 10135090 |

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
 Ansell Healthcare Europe NV
 T: +32 (0) 2 528 74 00
 F: +32 (0) 2 528 74 01

Asia Pacific Region
 MY +603 8310 6688
 apac.medical@ansell.com
 CN: +86 21 38275000
 infochina@ansell.com
 JP: +813 5549 8151
 info.medical.jp@ansell.com

North America Region
 Ansell Healthcare Products LLC
 T: +1 800 800 0444
 F: +1 800 800 0445

Latin America & Caribbean Region
 BR +55 (11) 3356-3100
 latam.medical@ansell.com
 MX: +52 442 296 2050
 latam.medical@ansell.com
 CO: +57 1 288 3247
 latam.medical@ansell.com

Australia
 Ansell Limited
 T: +61 1800 337 041
 F: +61 1800 803 578

Russia
 Ansell PYC
 Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

