

Durable air-fed protective suit providing biological, chemical and respiratory protection.

- **Specialized protection:** The AlphaTec BSL4 gas-tight protective suit is specially designed for Level 4 Biological Safety Laboratories, providing protection against infectious agents like bacteria, viruses and fungi, as well as radioactive particles. Additionally, it offers protection against chemicals in liquid, aerosol and solid forms.
- **Added comfort:** Designed for use with an external air source, these gas-tight chemical protective suits allow for longer working hours and improved wearer comfort
- **High durability:** Made of strong polyester fabric, coated with PVC on both sides, AlphaTec BSL4 gas-tight suits are soft and durable

Industries

- Biosafety Labs Levels 1-4
- Centers for Disease Control and Prevention
- Life Sciences
- Chemical
- Mining
- Fire and Rescue
- Oil and gas


Applications

- Clinical Research
- Medical Research


KEY FEATURES & BENEFITS

- **Durable protective suit:** Designed and developed for Level 4 Biological Safety Labs
- **For use with an external air source:** Adds enhanced wearer comfort
- **Made of strong material:** Durable yet soft protective suit

Material Diagram



Seam Diagram



Product Information

Product Information	
Available Sizes	S, M, L, XL, 2XL
Color	Orange
Country Of Origin	Lithuania
Packaging Overview	Individually packaged
Product Material	Strong and flexible polyester fabric, coated with PVC on both sides.
Product Reference	BSL4
Standards Overview	<ul style="list-style-type: none">• EN 1073-1:2016 & A1:2018 (radioactive particle protection)• EN 14605:2005 + A1:2009, type 3 (liquid-tight)• EN 14126:2003 (infective agent protection)• EN 1149-5:2008 (antistatic suit material)
Seam Type	Double welded
Shelf Life	7 years

Suit components & accessories

Suit Components and Accessories	
Design Features	Encapsulating, air-fed design for use with external air supply via airline. Fitted with a D-ring on top of the hood, to be able to hang the suit on a hook.
Visor And Face Seal	Extra large, wide vision visor (type VPI), made from a soft 1 mm transparent PVC.
Gloves And Attachments	Gloves are not fitted upon delivery, but the suit should be used with biological and chemical protective gloves. The suit is fitted with a rigid plastic ring (small ring for size S-M / large ring for size L-2XL), over which the glove is pulled and then secured with waterproof tape or a rubber band.
Footwear And Attachments	Welded-in socks (without boot flaps) made from the suit material. Alternatively attached PVC safety boots approved according to EN 20345. The boots are fixed with an ergonomically designed ring attachment, for simplified boot exchange.
Zipper	Heavy duty gas-tight zipper coated with PVC. Placed on the front left-hand side of the suit to facilitate donning and doffing. Closes downwards to give the wearer the possibility to check zipper position (closed or open). D-rings are fitted to either end of the zipper, for better grip and easy opening and closing.
Ventilation	<ul style="list-style-type: none"> • Airline Passthrough: A swiveling airline passthrough - the AlphaTec® BSL4 valve - placed on the right-hand side of the suit. The passthrough is fitted with a handle for adjusting the air flow & a low-flow warning whistle • External connection to air source: The airline passthrough is externally threaded for fitting of a HEPA filter and/or an air-line hose (not included). • Air Distribution: Air is distributed in front of the visor as well as into sleeves and legs. Excess air is ventilated through six (6) exhaust valves in the back of the hood & shoulders. The exhaust valves are fitted in a splash protective pocket. • Air Supply System: The air supply source, mobile or stationary, shall have a working/inlet pressure of 3.5 - 6 bar (51 - 87 psi). Min air flow rate > 260 l/min at 3.5 bar (51 psi) Max air flow rate < 630 l/min at 6 bar (87 psi) NOTE: The delivered air shall fulfill the requirements for breathing air according to local regulations.
Included With Each Delivery	<ul style="list-style-type: none"> • 1 pce grease stick for lubrication of the zipper • 1 pair of comfort silicone oversocks (only for suits with sewn-in socks) • 1 pce coat hanger

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
 Ansell Healthcare Europe NV
 T: +32 (0) 2 528 74 00

North America Region
 Ansell Healthcare Products LLC
 T: +1 800 800 0444

Australia
 Ansell Limited
 T: +61 1800 337 041

Asia Pacific Region
 Ansell Global Trading Center
 T: +603 8310 6688

Latin America & Caribbean Region
 Ansell Commercial Mexico S.A. de C.V.
 T: +52 442 248 1544 / 248 3133

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

