

55-105Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

NRL RABS/isolator gloves, with certified tear and abrasion resistance

Port size: 203mm/8"
Thickness: 0.76mm/30 mil

- Sustained protection: AlphaTec® NRL RABS and Isolator Gloves 55-105 satisfy EN388:2016 standards for Level 2 tear and abrasion resistance
- Improved durability: Heavyweight thickness means they boast enhanced durability, for longer-lasting wear
- Limited contamination risks: These RABS gloves are susceptible to fewer contamination risks and easy to keep clean, thanks to their unlined and translucent design

KEY FEATURES & BENEFITS

- EN388:2016 compliance: For tear- and abrasion-resistant safety gloves
- Heavyweight thickness: Enhanced durability, for longer glove life
- **Unlined:** Fewer contamination risks and easier cleaning







55-105

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

TECHNICAL DATA SHEET

Product Reference	55-105
Material	Natural Rubber Latex
Color	Natural
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	10
Temperature Range	From -30°C to 50°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN ISO 374-5:2016, EN 388:2016, Category III, UKCA
Vulcanization Chemical Accelerators	 Natural rubber proteins Zinc Diethyldithiocarbamate (ZDEC)





55-105 Non-clean/Non-sterile Latex (

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

PHYSICAL PROPERTIES

	Typical Values	Testing Method
Typical Length (mm/in)	813 / 32	EN 455-2
Port Size	203mm/8"	
Target Single Wall Palm Thickness (mm/mil)	0.76 / 30	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.76 / 30	EN 455-2

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level
Abrasion Resistance	Level 2
Blade Cut Resistance	Level 1
Tear Resistance	Level 2
Puncture Resistance	Level 1
ISO 13997 Cut Resistance	Level A

ORDERING INFORMATION

	PORT SIZE	8"/203mm
	SIZE	10
55-105	REORDER NO.	55105100

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890 Performance Standards and Regulatory Compliance











Ansell, $^{\circledR}$ and $^{\intercal}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\circledR}$ 2025 Ansell Limited. All Rights Reserved.

