

55-110Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

NRL RABS/Isolator gloves, for hand protection with heightened tear and abrasion resistance

Port size: 305mm/12"
Thickness: 0.51mm/20 mil

- Sustained protection: AlphaTec® NRL RABS and Isolator Gloves 55-110 meet EN 388:2016 Level 2 standards for tear and abrasion resistance
- Improved dexterity: Medium-level thickness offers these isolator gloves greater dexterity, making them ideal for daily repetitive applications
- Limited contamination risks: As they are unlined, absorption of chemical substances and subsequent contamination is less likely, while their translucent design facilitates cleaning

KEY FEATURES & BENEFITS

- EN388:2016 compliance: Elevated resistance against tears and abrasion
- Medium thickness: Enhanced dexterity, for easier parts handling
- Unlined: Reduced contamination risks and easy to clean







55-110

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

TECHNICAL DATA SHEET

| Product Reference | 55-110 |
|--|---|
| Material | Natural Rubber Latex |
| Color | Natural |
| Shape | Ambidextrous |
| External Glove Surface | Smooth |
| Cuff Style | Beaded |
| Storage Instructions | Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use. |
| Available Sizes | 10 |
| Temperature Range | From -30°C to 50°C |
| Shelf Life | Three (3) years from date of manufacture. |
| Standards | CE 0493, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN ISO 374-5:2016, EN 388:2016, Category III, UKCA |
| Vulcanization Chemical Accelerators | Natural rubber proteins Zinc Diethyldithiocarbamate (ZDEC) |





55-110Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

PHYSICAL PROPERTIES

| | Typical Values | Testing Method |
|---|----------------|----------------|
| Typical Length (mm/in) | 813 / 32 | EN 455-2 |
| Port Size | 305mm/12" | |
| | | |
| | | |
| Target Single Wall Palm Thickness (mm/mil) | 0.51 / 20 | EN 455-2 |
| Target Single Wall Cuff Thickness (mm/mil) | 0.51 / 20 | EN 455-2 |

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

| Risk | Performance level |
|--------------------------|-------------------|
| Abrasion Resistance | Level 2 |
| Blade Cut Resistance | Level O |
| Tear Resistance | Level 2 |
| Puncture Resistance | Level O |
| ISO 13997 Cut Resistance | Level A |

ORDERING INFORMATION

| | PORT SIZE | 12"/305mm |
|--------|-------------|-----------|
| | SIZE | 10 |
| 55-110 | REORDER NO. | 55110100 |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Performance Standards and Regulatory Compliance









Ansell, $^{\textcircled{8}}$ and $^{\textcircled{m}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{c}}$ 2025 Ansell Limited. All Rights Reserved.

