

73-701

Sterile Disposable Neoprene (Polychloroprene) Cleanroom Glove

Sterile neoprene disposable gloves, designed for use in aseptic and Class 100 (ISO 5)/Grade A cleanroom environments

- Improved durability: TouchNTuff®
 DermaShield™ 73-701 sterile disposable gloves boast a unique neoprene formulation, resulting in greater durability and puncture resistance
- Reduced allergy risks: Designed for aseptic environments and free of latex proteins and chemical accelerators, these neoprene gloves prevent the risk of Type I and Type IV allergies and sensitivities
- Enhanced features: Their beaded cuff, designed with SUREFIT[™] Cuff Roll-Down Technology, prevents cuffs from rolling down, facilitating sustained wear
- Heightened protection: Beyond robustness, these neoprene gloves offer wearers high levels of chemical splash resistance, protecting hands from various hazards



KEY FEATURES & BENEFITS

- Neoprene formulation: Excellent puncture resistance and durability
- SUREFIT[™] Technology: Lesser risk of cuff roll-down
- Latex-free, chemical accelerator-free:
 Type I and Type IV allergy risks
 eliminated

Industries

- Pharmaceutical Manufacturing
- Laboratory Research and Development
- Biotechnology Manufacturing
- Controlled and Critical Environments
- Production and Manufacturing

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Blending, compounding solids and liquids
- Aseptic filling and labelling





73-701

Sterile Disposable Neoprene (Polychloroprene) Cleanroom Glove

TECHNICAL DATA SHEET

	Product Information
Material	Neoprene (Polychloroprene)
Color	Green
Shape	Anatomic with Curved Fingers
Cuff	Straight with SUREFIT™ Technology
Manufacturing/QMS Audit Standards	ISO 9001:2015
Regulatory/Standard Compliance	21 CFR § 820 Quality System regulations, AS/NZS 4179, ASTM D3577, ASTM D7160, CE 0493, EN 421:2010, EN 556-1:2001, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN 374-2 and -4, EN ISO 374-5:2016, ISO 10282, ISO 11193, ISO 13485, ISO 14001, ISO 9001:2015, UKCA
	1 pair per inner wrap; one inner wrap per smart pack; 25 smart packs per inner bag; 2 inner bags per outer bag; 4 outer bags per lined carton; 200 pairs per carton
Packaging	More sustainable packaging: These sterile gloves are packed in recyclable plastic packaging* and delivered in recycled cardboard shipper cases.
	*Inner wrap, smart pack, pouch, bag and liner are made from polyethylene (PE) based film. Always check your local recyclable status as these materials may not be considered suitable for recycling in your location.
Storage	Keep away from direct sunlight; store in a dry place and keep in the original packaging. Keep away from ozone sources. If products are properly stored, as indicated, they won't lose their performances or change characteristics significantly. If products could be affected by ageing or storage, the expiry date is mentioned on the packaging materials.
Country of Origin	Malaysia
Available sizes	5.5, 6, 6.5, 7, 7.5, 8, 8.5, 9
Powder Content	Powder-Free
External Glove Surface	Textured Fingers
Internal Glove Surface	Polymer Coated with DERMASHIELD™ Technology
Sterilization Method	GAMMA irradiation (25 kGy)
Cleanroom Class	Class 100/ISO Class 5 & EU GMP Grade A/B and other sterile cleanrooms
Shelf Life	5 years
Tested for use with Chemotherapy Drugs	Yes, in accordance with ASTM D6978 (Not listed in the US FDA 510k)
Protein Level	N/A: contains no natural rubber latex
Anti-static	No
Vulcanization Chemical Accelerators	• None





73-701

Sterile Disposable Neoprene (Polychloroprene) Cleanroom Glove

Physical Properties									Testing Method	
Sizes	5.5	6	6.5	7	7.5	8	8.5	9		
Typical Length (mm/in)	295 / 11.6							EN 420/ASTM D3767		
Palm Width (mm/in)	73/2.87	78/3.07	84/3.31	90/3.54	96/3.78	103/4	109.5/4	3117/4.6		
Freedom from Holes	0.65 AQL								EN 455-1/ASTM D3577	
Typical Particle Count ≥0.5µm (counts / cm²)	≤ 3500							IEST-RP-CC005.4		
Target Single Wall Palm Thickness (mm/mil)	0.19 / 7.5							EN 420/ASTM D3767		
Target Single Wall Finger Thickness (mm/mil)	0.21 / 8.27							EN 420/ASTM D3767		
Target Single Wall Cuff Thickness (mm/mil)	0.15/5.9							EN 420/ASTM D3767		
Ultimate tensile strength (MPa) Before Aging	17							ASTM D412-06a		
Ultimate tensile strength (MPa) During Aging	12							ASTM D412-06a		
Force at Break (N) Before Aging	9							EN 455-2		
Force at Break (N) During Aging	9							EN 455-2		

ORDERING INFORMATION

SIZE	5.5	6	6.5	7	7.5	8	8.5	9
REORDER NO.	73701055	73701060	73701065	73701070	73701075	73701080	73701085	73701090

PERFORMANCE STANDARDS AND REGULATORY COMPLIANCE













For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Technology





Cuff Roll-down Technology

Ansell, $^{\textcircled{R}}$ and $^{\textcircled{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{M}}$ 2024 Ansell Limited. All Rights Reserved.

