

## Chemical-resistant CSM gloves, offering lasting hand protection

Port size: 203mm/8"

Thickness: 0.6mm/24 mil

- **Advanced defenses:** The AlphaTec® CSM Isolator Glove 85-301 is highly resistant to most concentrated acids and bases, while its 0.6mm/24 mil thickness ensures greater hand protection than thinner alternatives
- **Elevated comfort:** These CSM gloves are composed of soft, flexible material for ease of use
- **Prolonged glove life:** The AlphaTec® CSM Isolator Glove 85-301 can withstand prolonged exposure to oxygen, UV rays and ozone without rapidly aging, and it boasts EN 388:2016+A1:2018 Level 3 abrasion resistance
- **Limited contamination risks:** Their white coloring also makes contamination easy to detect



### KEY FEATURES & BENEFITS

- **Tough CSM composition:** Guards against concentrated acids and bases
- **Flexible material:** For ease of use and wearer comfort
- **Hard-wearing design:** Unfazed by oxygen, UV ray and ozone exposure

### TECHNICAL DATA SHEET

Product Reference	85-301
Material	Chlorosulfonated polyethylene_CSM
Color	White
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 120°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-5:2016, EN ISO 374-1:2016 Type B, Category III
Vulcanization Chemical Accelerators	<ul style="list-style-type: none"><li>None</li></ul>

### PHYSICAL PROPERTIES

	Typical Values	Testing Method
Typical Length (mm/in)	800 mm / 32"	EN ISO 21420
Port Size	8"	
Target Single Wall Palm Thickness (mm/mil)	0.6mm / 24 mil	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.6 mm / 24 mil	EN 455-2

### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level
Abrasion Resistance	Level 3
Blade Cut Resistance	Level 1
Tear Resistance	Level 0
Puncture Resistance	Level 1

### ORDERING INFORMATION

	PORT SIZE	8"/203mm	8"/203mm
	SIZE	9.5	11
85-301	REORDER NO.	85301095	85301110

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### Asia Pacific Region

Ansell Global Trading Center  
T: +603 8310 6688  
F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC  
US T: +1 800 800 0444  
US F: +1 800 800 0445  
CA T: +1-800-363-8340

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

#### UK

Ansell Nitritex  
T: +44 1638 663338  
F: +44 1638 668890

### Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.