

**85-307** Non-clean/Non-sterile CSM RABS/Isolator Gloves

## Chemical-resistant CSM gloves granting durable and comfortable hand protection

Port size: 10" Thickness: 0.6mm/24 mil

- Advanced defenses: The AlphaTec® CSM Isolator Gloves 85-307 Size 11/XL is designed for high resistance against concentrated acids and bases
- Elevated comfort: Owing to their soft and flexible material, these chemicalresistant gloves grant ease of use
- Improved durability: In addition to resisting ageing from exposure to oxygen, UV rays and ozone, these hand protection gloves withstand temperatures between -20°C and 120°C
- Reduced contamination risks: The AlphaTec® CSM Isolator Gloves 85-307 Size 11/XL comes in white, which ensures the easy detection of contamination
- Added safety: These protective gloves are also washed to eliminate talcum residue, reinforcing personal protection

#### **KEY FEATURES & BENEFITS**

- Sturdy CSM composition: Protects from concentrated acids and bases
- Soft and flexible material: Comfortable safety gloves
- Durable design: Resists ageing from oxygen, UV ray and ozone exposure





### AlphaTec® Advanced chemical protection

**85-307** Non-clean/Non-sterile CSM RABS/Isolator Gloves

#### **TECHNICAL DATA SHEET**

Product Reference	85-307
Material	Chlorosulfonated polyethylene_CSM
Color	White
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11
Temperature Range	From -20°C to 120°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN 420:2003 + A1:2009, Category III
Vulcanization Chemical Accelerators	None

# AlphaTec®

**85-307** Non-clean/Non-sterile CSM RABS/Isolator Gloves

#### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	850 mm / 33"	EN ISO 21420
Port Size	10"	
Target Single Wall Palm Thickness (mm/mil)	0.6 mm / 24 mil	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.6 mm / 24 mil	EN 455-2

#### **PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018**

Risk	Performance level
Abrasion Resistance	Level 3
Blade Cut Resistance	Level 1
Tear Resistance	Level O
Puncture Resistance	Level 1

#### **ORDERING INFORMATION**

	PORT SIZE	10"/254mm
	SIZE	11
85-307	REORDER NO.	85307110

#### For additional information visit us at www.ansell.com, or call us at

#### **Europe, Middle East & Africa Region** Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

**Asia Pacific Region** Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

CA T: +1-800-363-8340 Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

#### Performance Standards and Regulatory Compliance



3101A

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

