



Oil

Low Chemical Protection



Light Duty

Lightweight abrasion-resistant gloves with advanced oil-repellent capabilities

- **Specialized protection:** HyFlex® 11-926 industrial safety gloves possess a RIPEL™ Liquid Repellence surface barrier, which prevents skin contact with oil or chemicals, ensuring workplace safety
- **Enhanced grip:** These HyFlex® gloves' three quarter-dipped coating and force-minimizing ANSELL GRIP™ treatment enhances their grip performance
- **Increased flexibility:** HyFlex® 11-926 industrial gloves' ergonomic hand shape and lightweight liner help diminish hand fatigue by making them flexible and maneuverable
- **Elevated comfort:** Spandex® and nylon combine to grant the HyFlex® 11-926's liner a "second skin" feel, for light, comfortable handling
- **Improved durability:** HyFlex® 11-926 industrial working gloves achieve ANSI/ISEA 105-2024 ABRASION LEVEL 3 and EN ABRASION LEVEL 4 standards, for long-lasting wear



Industries

- Automotive
- Machinery and Equipment
- Metal fabrication
- Chemical
- Agriculture

Applications

- Metalworking & assembly operations
- Picking, fastening components
- Production line support & maintenance
- Assembling and mounting components
- Loading and unloading rough parts or boxes
- Changing tools and dies
- Final assembly
- Assembly & inspection of components
- Assembly and disassembly of equipment
- Warehousing of raw materials
- Loading and unloading trucks and vehicles
- Handling incoming goods
- Opening furnaces draining pumps valves or lines and crackers BTX process

HyFlex®

ADVANCED MECHANICAL PROTECTION

11-926

Light duty oil repellent, oil grip multi-purpose glove

Key Features

- **RIPEL™ Liquid Repellence:** Safety gloves adapted to oily conditions
- **Three-quarter dipping:** For protective coating with secure grip
- **Lightweight fine-gauge liner:** Offering flexibility and comfort

Vulcanization Chemical Accelerators

- Zinc Dibutyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

Performance Standards & Regulatory Compliance

ANSI/ISEA 105-2024



EN388: 2016



4121A



GR
ISO 18889

EN 388



4121

EN 388



4121A



Specifications

BRAND STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
HyFlex® 11-926	Finishing: ¾ Coated Coating Material: Nitrile Liner Material: Nylon Cuff Style: Knitwrist	18	6, 7, 8, 9, 10, 11	215-260 mm/ 8.46-10.23 inches	Purple	12 pairs/bag, 12 bags/carton

Technologies



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

North America Region

Ansell Healthcare Products LLC
111 Wood Avenue South,
Suite 900
Iselin, NJ 08830, USA
T: +1 800 800 0444
F: +1 800 800 0445

Australia

Ansell Limited
Level 3,678 Victoria Street,
Richmond, Vic, 3121
Australia
T: +61 1800 337 041
F: +61 1800 803 578

Asia Pacific Region

Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
T: +603 8310 6688
F: +603 8310 6699

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
Blvd. Bernardo Quintana No. 7001-C,
Q7001 Torre II,
Suites 1304, 1305 y 1306,
Col. Centro Sur, c.p. 76079
Queretaro, Qro. Mexico
T: +52 442 248 1544 / 248 3133

Canada

Ansell Canada
105 Lauder
Cowansville, QC J2K 2K8
Canada
T: +1 800 363 8340
F: +1 800 267 3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

