

Previously known as: Puretough™P5000



Cut



Medium Duty

Abrasion-resistant gloves, with color coding to ensure appropriate application

- **Indicated protection levels:** HyFlex® 11-425 industrial gloves follow a color-coded indicator system, helping workers identify when to use them safely
- **Prolonged durability:** HyFlex® 11-425 industrial safety gloves boast ANSI level 6 and EN level 4 abrasion resistance
- **Added grip and eco-friendliness:** The HyFlex® 11-425's PU and nitrile coating provides strong grip and is water-based, for a more environmentally friendly fabrication process
- **Advanced defenses and comfort:** INTERCEPT™ Cut Resistance Technology yarn provides EN ISO C/ANSI A3 cut protection, while seamless knitting means hand protection with greater comfort
- **Guaranteed convenience:** These industrial gloves are available in vend pack form, facilitating rapid access
- **Certified skin-friendliness:** Dermatest® certification ensures these PPE gloves are skin-friendly



Industries

- Automotive
- Chemical
- Food Processing

Applications

- Handling metal sheets & panels
- Handling parts with sharp, rough edges
- Applying sealers, touching up
- Production line support & maintenance
- Loading and unloading trucks and vehicles
- Product shipping, transport and delivery
- Maintenance
- Opening furnaces draining pumps valves or lines and crackers BTX process
- Lock smith

HyFlex[®]

ADVANCED MECHANICAL PROTECTION

11-425

Designed to make the selection of hand protection easy

Previously known as: Puretough™P5000

Key Features

- **HyFlex[®] indicator system:** Workers can ensure adequate protection
- **Certified abrasion resistance:** Excellent durability
- **Water-based PU and nitrile coating:** Enhanced grip and comfort

Vulcanization Chemical Accelerators

- Natural rubber proteins (in knitwrist elastic)
- Zinc Diethyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

Performance Standards & Regulatory Compliance



Technologies



DMF free



INTERCEPT™
Cut Resistance Technology

Specifications

| BRAND STYLE | DESCRIPTION | Gauge | SIZE | LENGTH | COATING COLOR | PACKAGE |
|----------------------------|---|-------|--------------------|-------------------------------|---------------|------------------------------|
| HyFlex [®] 11-425 | Finishing: Palm Coated Coating Material: Water-Based polyurethane and nitrile Liner Material: Polyamide, Fiber glass, HPPE Cuff Style: Knitwrist | 13 | 6, 7, 8, 9, 10, 11 | 225-270 mm; 8.86-10.62 inches | Grey | 12 pairs/bag, 12 bags/carton |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

North America Region

Ansell Healthcare Products LLC
111 Wood Avenue South,
Suite 900
Iselin, NJ 08830, USA
T: +1 800 800 0444
F: +1 800 800 0445

Australia

Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
T: +61 1800 337 041
F: +61 1800 803 578

Asia Pacific Region

Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
T: +603 8310 6688
F: +603 8310 6699

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
Blvd. Bernardo Quintana No. 7001-C,
Q7001 Torre II,
Suites 1304, 1305 y 1306,
Col. Centro Sur, c.p. 76079
Queretaro, Qro. Mexico
T: +52 442 248 1544 / 248 3133

Canada

Ansell Canada
105 Lauder
Cowansville, QC J2K 2K8
Canada
T: +1 800 363 8340
F: +1 800 267 3551

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

