

73-500 Sterile Disposable Neoprene (Polychloroprene) Cleanroom Glove

Sterile neoprene disposable gloves, compatible with Class 100(ISO5)/Grade A cleanroom environments

- Double donning capability: TouchNTuff® 73-500 latex-free sterile gloves are designed to enable effortless donning, making them ideal for double gloving applications
- Specialized protection: These neoprene cleanroom gloves deliver excellent chemical splash resistance against a broad range of hazards
- Reduced allergy risks: They are also free from latex proteins and chemical accelerators, reducing wearers' susceptibility to Type I or Type IV allergic reactions
- Sterility assurance: These cleanroom gloves are also sterilised by gamma irradiation, with a sterility assurance level (SAL) of 10-6

KEY FEATURES & BENEFITS

- Class 100 (ISO 5) cleanroom compatibility: Assured cleanliness
- Latex-free, chemical accelerator-free: Fewer allergy risks
- Hard-wearing neoprene formulation: Chemical splash resistance and durability

Industries

- Pharmaceutical Manufacturing
- Medical Device Manufacturing
- Laboratory Research and Development
- Controlled and Critical Environments
- Production and Manufacturing

Recommended For

- Packaging and labeling
- Clean room cleaning and
- preparing
- Sample taking and processing





WWW.ANSELL.COM

TouchNTuff® Advanced product & worker protection

73-500 Sterile Disposable Neoprene (Polychloroprene) Cleanroom Glove

TECHNICAL DATA SHEET

	Product Information			
Material	Neoprene (Polychloroprene)			
Color	Cream			
Shape	Anatomic with Curved Fingers			
Cuff	Beaded with SUREFIT™ Technology			
Manufacturing/QMS Audit Standards	ISO 9001:2015			
Regulatory/Standard Compliance	AS/NZS 4179, ASTM D3577, ASTM D7160, CE 0493, EN 556-1:2001, EN ISO 21420:2020, EN ISO 374-1:2016 Type B (KLT), EN ISO 374-5:2016, EN 421:2010, ISO 10282, ISO 11193, ISO 13485, UKCA			
	1 pair per inner poly pack; 10 inner poly packs per inner polybag; 5 outer polybags per bag; 4 bags per master bag; 1 master bag of 200 pairs per carton/case			
Packaging	More sustainable packaging: These sterile gloves are packed in recyclable plastic packaging* and delivered in recycled cardboard shipper cases.			
	*Inner wrap, pouch, bag and liner are made from polyethylene (PE) based film. Always check your local recyclable status as these materials may not be considered suitable for recycling in your location.			
Storage	Keep away from direct sunlight; store in a dry place and keep in the original packaging. Keep away from ozone sources. If products are properly stored, as indicated, they won't lose their performances or change characteristics significantly. If products could be affected by ageing or storage, the expiry date is mentioned on the packaging materials.			
Country of Origin	Sri Lanka			
Available sizes	5.5, 6, 6.5, 7, 7.5, 8, 8.5, 9			
Powder Content	Powder-Free			
External Glove Surface	Smooth			
Internal Glove Surface	Polymer Coated with DERMASHIELD™ Technology			
Sterilization Method	GAMMA irradiation (25 kGy)			
Cleanroom Class	Class 100/ISO 5 & EU GMP Grade A			
Shelf Life	5 Years			
Tested for use with Chemotherapy Drugs	Yes, in accordance with ASTM D6978 (Not listed in the US FDA 510k)			
Protein Level	N/A: contains no natural rubber latex			
Anti-static	No			
Vulcanization Chemical Accelerators	None			



TouchNTuff® ADVANCED PRODUCT & WORKER PROTECTION

73-500 Sterile Disposable Neoprene (Polychloroprene) Cleanroom Glove

Physical Properties		Testing Method
Typical Length (mm/in)	300 / 12	EN ISO 21420 ASTM D3767
Freedom from Holes	0.65 AQL	EN 455-1/ASTM D3577
	0.05 AQL	EN 455-1/ASTM D5577
Typical Particle Count ≥0.5µm (counts / cm²)	≤ 2500	IEST-RP-CC005.4
Target Single Wall Palm Thickness (mm/mil)	0.15 / 5.90	EN ISO 21420/ASTM D3767
Target Single Wall Finger Thickness (mm/mil)	0.16 / 6.29	EN 420/ASTM D3767
Target Single Wall Cuff Thickness (mm/mil)	0.14 / 5.51	EN 420/ASTM D3767
Ultimate tensile strength (MPa) Before Aging	17	ASTM D412-06a
Ultimate tensile strength (MPa) During Aging	12	ASTM D412-06a
Force at Break (N) Before Aging	9	EN 455-2
Force at Break (N) During Aging	9	EN 455-2

ORDERING INFORMATION

SIZE	5.5	6	6.5	7	7.5	8	8.5	9
REORDE NO.	^२ 73500055	73500060	73500065	73500070	73500075	73500080	73500085	73500090

PERFORMANCE STANDARDS AND REGULATORY COMPLIANCE



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133 Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 UK Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890 Technology



Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

