

85-301Non-clean/Non-sterile CSM RABS/Isolator Gloves

Chemical-resistant CSM gloves, offering lasting hand protection

Port size: 203mm/8"
Thickness: 0.6mm/24 mil

- Advanced defenses: The AlphaTec® CSM Isolator Glove 85-301 is highly resistant to most concentrated acids and bases, while its 0.6mm/24 mil thickness ensures greater hand protection than thinner alternatives
- Elevated comfort: These CSM gloves are composed of soft, flexible material for ease of use
- Prolonged glove life: The AlphaTec® CSM Isolator Glove 85-301 can withstand prolonged exposure to oxygen, UV rays and ozone without rapidly aging, and it boasts EN 388:2016 Level 3 abrasion resistance
- Limited contamination risks: Their white coloring also makes contamination easy to detect

KEY FEATURES & BENEFITS

- Tough CSM composition: Guards against concentrated acids and bases
- Flexible material: For ease of use and wearer comfort
- Hard-wearing design: Unfazed by oxygen, UV ray and ozone exposure







85-301Non-clean/Non-sterile CSM RABS/Isolator Gloves

TECHNICAL DATA SHEET

Product Reference	85-301
Material	Chlorosulfonated polyethylene_CSM
Color	White
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 120°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-5:2016, EN ISO 374-1:2016 Type B, Category III, UKCA
Vulcanization Chemical Accelerators	None





85-301Non-clean/Non-sterile CSM RABS/Isolator Gloves

PHYSICAL PROPERTIES

	Typical Values	Testing Method
Typical Length (mm/in)	800 / 32	EN ISO 21420
Port Size	203mm/8"	
Target Single Wall Palm Thickness (mm/mil)	0.6 / 24	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.6 / 24	EN 455-2

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level	
Abrasion Resistance	Level 3	
Blade Cut Resistance	Level 1	
Tear Resistance	Level O	
Puncture Resistance	Level 1	
ISO 13997 Cut Resistance	Level A	

ORDERING INFORMATION

	PORT SIZE	8"/203mm	8"/203mm
	SIZE	9.5	11
85-301	REORDER NO.	85301095	85301110

Performance Standards and Regulatory Compliance









For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133 Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890



Ansell, $^{\circledR}$ and $^{\intercal}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\circledR}$ 2025 Ansell Limited. All Rights Reserved.

