

**85-502** Non-clean/Non-sterile EPDM RABS/Isolator Gloves

# EPDM RABS/isolator gloves, made with premium FDA-approved material, for fewer glove changes

Port size: 254mm/10" Thickness: 0.4mm/16 mil

- Optimized durability: The AlphaTec® EPDM Isolator Glove 85-502 is designed for repeated autoclave sterilization (up to 50 times), which means fewer replacements
- Assured protection: These RABS gloves are EN ISO 374-compliant, resisting hydrogen peroxide and common disinfecting chemicals
- Increased eco-friendliness: They are halogen-free, making them suitable for disposal by incineration
- Food handling compliance: They comply with FDA Food Contact regulation (FDA Positive List) 21 CFR 177 for Indirect Food Additives

#### **KEY FEATURES & BENEFITS**

- EPDM material: Ideal for repeated autoclave sterilization
- Chemical resistance: Hydrogen peroxide/common disinfecting chemicals
- FDA food handling compliance: For safe, assured food handling





# AlphaTec® Advanced chemical protection

# **85-502** Non-clean/Non-sterile EPDM RABS/Isolator Gloves

# **TECHNICAL DATA SHEET**

Product Reference	85-502
Material	Ethylene propylene diene rubber_EPDM
Color	Black
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 130°C
Cleanroom Class	Non-Critical Environment
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-1:2016 Type B, EN ISO 374- 5:2016, Category III, UKCA
Vulcanization Chemical Accelerators	<ul> <li>Diphenyl guanidine</li> <li>Tetramethylthiuram disulfide</li> </ul>

# Alpha **EC**<sup>®</sup> ADVANCED CHEMICAL PROTECTION

85-502 Non-clean/Non-sterile EPDM **RABS/Isolator Gloves** 

## **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	800/32	EN ISO 21420
Port Size	254mm/10"	
Target Single Wall Palm Thickness (mm/mil)	0.40 / 16	EN 455-2
Target Single Wall Finger Thickness (mm/mil)	0.40 / 16	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.40 /16	EN 455-2

### **PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018**

Risk	Performance level	
Abrasion Resistance	Level 2	
Blade Cut Resistance	Level 1	
Tear Resistance	Level 1	
Puncture Resistance	Level 1	
ISO 13997 Cut Resistance	Level A	

#### **ORDERING INFORMATION**

	PORT SIZE	10"/254mm	10"/254mm
	SIZE	9.5	11
85-502	REORDER NO.	85502095	85502110

#### **Performance Standards and Regulatory Compliance**

15





UK

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Europe, Middle East & Africa Region

North America Region Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

For additional information visit us at www.ansell.com, or call us at

Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 UΚ

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

