

11-427

Designed to make the selection of hand protection easy

Previously known as: Puretough™P3000TROPIQUE







Cut

ıt Hea

Medium Duty

Abrasion-resistant medium-duty safety gloves, offer wearers heat and cut resistance

- Improved durability: HyFlex® 11-427 are mediumduty gloves with a durable polyurethane/nitrile coating that meets EN and ANSI/ISEA 105-2024 ABRASION LEVEL 4 standards
- Increased eco-friendliness: Their PU/nitrile coating is made using a more environmentally conscious water-based process
- Reduced surface defect risks: Their silicone-free design eliminates the risk of related contaminant transfer to metal when painting
- Minimized health risks: These HyFlex[®] gloves' DMF-free formulation prevents potential health risks
- Enhanced defenses: Their high-visibility, highperformance fibers ensure contact heat resistance up to 100°C/212°F
- Easy identification: The orange color-coded indicator button signifies that these gloves meet ANSI/ISEA 105-2024 CUT A2 and EN ISO B standards



Industries

- Automotive
- Chemical

Applications

- Handling metal sheets & panels
- Handling parts with sharp, rough edges
- Applying sealers, touching up
- Production line support & maintenance
- Loading and unloading trucks and vehicles
- Handling incoming goods
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Loading trucks & vehicles
- Product shipping, transport and delivery
- Maintenance
- Lock smith





11-427

Designed to make the selection of hand protection easy

Technologies

Previously known as: Puretough™P3000TROPIQUE

INTERCEPT Cut Resistance Technology

Key Features

- Water-based polyurethane coating: Durable, but more eco-
- DMF- and silicone-free: Fewer health risks, suited to spray-painting
- **High-visibility, high-performance fibers:** Heat* and cut resistance contact heat resistance up to 100°C/212°F

Vulcanization Chemical Accelerators

- Natural rubber proteins (in knitwrist elastic)
- Zinc Diethyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

Performance Standards & Regulatory Compliance



ANSI/ISEA 105-2024







4X32B





Specifications

BRAND STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
	Finishing: ¾ Coated Coating Material: Water-Based polyurethane and nitrile Liner Material: Polyamide, Fiber glass Cuff Style: Knitwrist	13	7, 8, 9, 10	235-260mm; 9.25-10.23 inches	Grey	12 pairs/bag, 12 bags/carton

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Ansell Healthcare Europ Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. Blvd. Bernardo Quintana No. 7001-C, BIVA. Bernardo Quintana No. 70 Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

North America Region

Ansell Healthcare Products LLC 111 Wood Avenue South, Suite 900 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Canada

Ansell Canada 105 Lauder Cowansville, QC J2K 2K8 T: +1 800 363 8340 F: +1 800 267 3551

Australia

Ansell Limited Ansell Limited Level 3,678 Victoria Street, Richmond, Vic, 3121 Australia T: +61 1800 337 041 F: +61 1800 803 578

Asia Pacific Region

Ansell Global Trading Center Ansell Global Trading Center (Malaysia) Sdn Bhd Prima 6, Prima Avenue Block 3512, Jalan Teknokrat 6 T: +603 8310 6688 F: +603 8310 6699

Ansell, $^{@}$ and m are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{@}$ 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

