

93-732

Ergonomically designed thin Black Nitrile exam glove

Nitrile exam gloves with excellent dexterity along with enhanced comfort, fit and feel

- Elevated comfort: These thin, black nitrile medical exam gloves offer enhanced dexterity and tactility in a thin, yet strong design
- Black nitrile: Distinctive black color provides contrast while also hiding the appearance of oils, bodily fluids and other stains
- ERGOFORM[™] Technology: ERGOFORM[™] Ergonomic Design Technology reduces muscle strain during repetitive tasks, improving worker comfort and productivity
- Optimized grip: Textured on the fingertips for secure handling of instruments and materials



Industries

- Food Service
- Cosmetics
- Tattoo
- Automotive Aftermarket
- Chemical
- Emergency Medical Services
- Healthcare
- Law Enforcement
- Life Sciences
- Dental
- Machinery and Equipment
- Metal fabrication

Recommended For

- General dentistry
- Standard patient examinations
- Emergency services
- Catering/Meal preparation
- General Purpose Auto Aftermarket
- Equipment repair and maintenance
- Laboratory analysis
- Cosmetic Procedures
- Tattoo



TECHNICAL DATA SHEET

	Product Information			
External Glove Surface	Textured Fingers			
Audit Standards	21 CFR 820, ISO 13485, ISO 9001			
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks			
Packaging Overview	Case=1000 gloves/10 dispensers; Dispenser=100 gloves 2XL: Case=900 gloves/10 dispensers; Dispenser=90 gloves			
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.			
Country Of Origin	China			
Product Segmentation	High Touch			
Antistatic	No			
Silicone Free	No			
Vulcanization Chemical Accelerators	 Zinc Dibutyldithiocarbamate (ZDBC) Zinc Diethyldithiocarbamate (ZDEC) Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions. 			

PHYSICAL PROPERTIES

	Typical	Testing Method	
Length (mm/inches)	245 / 9.6		ASTM D6319,EN 455-2
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D6319,EN 455-2
Finger Thickness (mm/mils)	0.11 / 4.3		ASTM D6319,EN 455-2
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 16	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412 & D573
Force at break (N)	≥6	≥6	EN 455

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	93732060	93732070	93732080	93732090	93732100	93732110

Performance Standards and Regulatory Compliance





















For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region
MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
IP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1288 3247 Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Technology



Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

