

83-500 Sterile Disposable Polyisoprene Cleanroom Glove

Sterile polyisoprene gloves, designed for Class 100 (ISO 5)/Grade A cleanroom environments

- Elevated comfort: Ideal for double gloving, TouchNTuff® 83-500 polyisoprene cleanroom gloves' ultrasoft polyisoprene offers "second skin"like comfort and minimizes hand fatigue with prolonged wear
- **Reduced allergy risks:** They contain no latex proteins, meaning they do not pose any threat related to Type I latex allergies and sensitivities
- Sterility assurance: These disposable gloves are sterilized by gamma irradiation, with a sterility assurance level (SAL) of 10-6



KEY FEATURES & BENEFITS

- Ultra-soft polyisoprene: "Second skin" comfort and feel
- Latex-free design: Latex Type I allergy risks eliminated
- Gamma sterilization: A sterility assurance level (SAL) of 10-6

Industries

- Laboratory Maintenance & Clean-Up
- Pharmaceutical Manufacturing
- Biotechnology Manufacturing
- Medical Device Manufacturing
- Laboratory Research and Development
- Preparation of Materials
- Production & Processing
- Lab and R&D
- Controlled and Critical
- EnvironmentsProduction and Manufacturing

- **Recommended For**
- Maintaining lab furniture and equipment
- Spill or leakage cleanup
- Transferring liquids and solids
- Packaging and labelingClean room cleaning and
- preparingSample taking and processing
- Administering drugs
- Transferring liquids and solids between vessels and tanks and process equipment





TouchNTuff® Advanced product & worker protection

83-500 Sterile Disposable Polyisoprene Cleanroom Glove

TECHNICAL DATA SHEET

	Product Information					
Material	PI (Polyisoprene)					
Color	White					
Shape	Anatomic with Curved Fingers					
Cuff	Beaded with SUREFIT [™] Technology					
Manufacturing/QMS Audit Standards	ISO 13485, ISO 9001:2015, Manufacturing QMS Audit Standards ISO 9001, PPE Regulation 2016 425 Module D					
Regulatory/Standard Compliance	AS/NZS 4179, ASTM D3577, ASTM D7160, CE 0493, EN 556-1:2001, EN ISO 21420:2020, EN ISO 374-1:2016 Type B (KPT), EN ISO 374-5:2016, EN 421:2010, Please consult the IFU, ISO 10282, ISO 11193, Category III, UKCA					
	1 pair per inner polybag; 10 pairs per outer polybag; 5 polybags per master polybags; 4 master polybags per carton; 200 pairs per carton					
Packaging	More sustainable packaging: These sterile gloves are packed in recyclable plastic packaging* and delivered in recycled cardboard shipper cases.					
	*Inner wrap, pouch, bag and liner are made from polyethylene (PE) based film. Always check your local recyclable status as these materials may not be considered suitable for recycling in your location.					
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.					
Country of Origin	Sri Lanka					
Available sizes	5.5, 6, 6.5, 7, 7.5, 8, 8.5, 9					
Powder Content	Powder-Free					
External Glove Surface	Smooth					
Internal Glove Surface	Polymer Coated with DERMASHIELD™ Technology					
Sterilization Method	GAMMA irradiation (25 kGy)					
Cleanroom Class	Class 100/ISO Class 5 & EU GMP Grade A/B and other sterile cleanrooms					
Shelf Life	5 Years					
Tested for use with Chemotherapy Drugs	Yes					
Protein Level	N/A: contains no natural rubber latex					
Anti-static	No					
Vulcanization Chemical Accelerators	 Xanthates Zinc Dialkyldithiocarbamate Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions. 					



TouchNTuff® Advanced product & WORKER PROTECTION

83-500 Sterile Disposable Polyisoprene Cleanroom Glove

Physical Properties		Testing Method
Typical Length (mm/in)	300 / 12	EN 420/ASTM D3767
Freedom from Holes	0.65 AQL	EN 455-1/ASTM D3577
Typical Particle Count ≥0.5µm (counts / cm²)	≤ 2500	IEST-RP-CC005.4
Target Single Wall Palm Thickness (mm/mil)	0.21 / 8.26	EN 420/ASTM D3767
Target Single Wall Finger Thickness (mm/mil)	0.23 / 9.05	EN 420/ASTM D3767
Target Single Wall Cuff Thickness (mm/mil)	0.17 / 6.69	EN 420/ASTM D3767
Ultimate tensile strength (MPa) Before Aging	≥17	ASTM D412-06a
Ultimate tensile strength (MPa) During Aging	≥12	ASTM D412-06a
Force at Break (N) Before Aging	9	EN 455-2
Force at Break (N) During Aging	9	EN 455-2

ORDERING INFORMATION

SIZE	5.5	6	6.5	7	7.5	8	8.5	9
REORDER NO.	83500055	83500060	83500065	83500070	83500075	83500080	83500085	83500090

PERFORMANCE STANDARDS AND REGULATORY COMPLIANCE



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133 Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 UK Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890 Technology



Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

