

Previously known as: MICROCHEM® 5000 - Model 151-G02

## Developed as a lightweight, Type 3 chemical protection solution for first responders and the emergency services..

- **Specialized protection:** The AlphaTec® 5000 Ultrasonically Welded & Taped - Model 151-G02 is a multi-layer rear-entry protective suit, resistant to chemicals, biological hazards and chemical warfare agents
- **Improved visibility:** Due to its bright orange in color, this chemical protective suit is highly noticeable, which enhances workplace safety, and is also usable as a HAZMAT suit
- **Heightened defenses:** Protection against liquid and particulate hazards is further enhanced by this protective suit's welded and taped seams
- **Enhanced features:** It features a neoprene rubber face seal that fits most full-face respirators, attached socks with boot overflaps, rear horizontal zip entry, as well as attached Ansell barrier gloves with oversleeves and finger loops
- **Certified antistatic capabilities:** This full body protection suit also satisfies EN 1149-5 antistatic standards

*\*CE Category III Type 3/4/5 protection*



## Industries

- Chemical
- Life Sciences
- Mining
- Fire and Rescue
- Oil and gas
- Automotive Aftermarket
- Emergency Medical Services
- Food Processing

## Applications

- Contaminated Environments
- Chemical Handling
- Filling, blending and charging of raw materials
- Transferring liquids and solids
- Opening and draining pumps valves or lines
- Loading and unloading of proces equipment
- Raw material sample collection
- Concentration mixing and palletisation
- Hazmat response
- Assembly and disassembly of large pipes

## KEY FEATURES & BENEFITS


- **Permeation barrier:** Resists harmful chemicals\* and biohazards
- **Highly visible orange color:** For reduced workplace injuries
- **Taped and welded seams:** Robust particulate and liquid resistance

\*>480-minute breakthrough time against 14 of the 15 chemicals listed in EN ISO 6529


## Technology



## Material Diagram



## Seam Diagram



## Performance Standards



## Product Information

Product Information	
Available Sizes	S, M, L, XL, 2XL, 3XL, 4XL, 5XL
Color	Orange
Country Of Origin	China
Packaging Overview	Individually Packed
Product Material	Multi-layer non-woven barrier Laminate fabric
Product Reference	5000 - Model 151-G02
Standards Overview	CE CATEGORY III (Type 3-B, Type 4-B, Type 5-B, EN 1073-2, EN 14126, EN 1149-5)
Seam Type	Welded and Taped
Shelf Life	5 years
Style Number	O50T151B

## Suit components & accessories

Suit Components and Accessories	
<b>Design Features</b>	Neoprene rubber face seal, rear horizontal zip entry, ultrasonically welded and taped seams. Attached socks with boot overflap and attached Ansell AlphaTec® 02-100 Gloves with oversleeves and finger loops.
<b>Gloves And Attachments</b>	AlphaTec® 02-100

**For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at**

**Europe, Middle East & Africa Region**

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00

**North America Region**

Ansell Healthcare Products LLC  
T: +1 800 800 0444

**Australia**

Ansell Limited  
T: +61 1800 337 041

**Asia Pacific Region**

Ansell Global Trading Center  
T: +603 8310 6688

**Latin America & Caribbean Region**

Ansell Commercial Mexico S.A. de C.V.  
T: +52 442 248 1544 / 248 3133

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

