

## 93-252

Distinctive, Black Nitrile Exam Glove

# Black nitrile gloves, for dirt-masking hand protection and superior grip

- Masks stains: MICROFLEX<sup>®</sup> 93-252 gloves' black color disguises dirt while enhancing the visibility of light-colored objects
- Enhanced grip: A fully textured, nonfoaming design offers these powderand silicone-free nitrile gloves superior grip
- Proven protection: These gloves comply with EN ISO 374 Type B chemical resistance standards, providing chemical splash protection
- Genuine versatility: These gloves are suitable for various applications, used notably by auto mechanics, maintenance workers and law enforcement officers
- Food handling compliant: Also ideal for a wide range of food handling applications



#### **Industries**

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment

#### **Recommended For**

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Use of cleaning tools and robotic equipment
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Blending, compounding solids and liquids
- Raw material sample collection
- Weighing and dispensing of solid and liquid raw materials
- Inspection (picking, checking and marking)



### **TECHNICAL DATA SHEET**

	Product Information
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, EN 1149-1/2/3, EN 420:2003 + A1:2009, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKT, FDA21 CFR 177-2600-US Food Contact Approved, ISO 11193, ISO 13485, ISO 9001
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	Robust
Antistatic	Yes
Silicone Free	Yes

#### **PHYSICAL PROPERTIES**

	Typical	Testing Method	
Length (mm/inches)	245 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	1.5 △	ASTM D5151,EN 455-1	
Palm Thickness (mm/mils)	0.12,	ASTM D3767,EN 420	
Finger Thickness (mm/mils)	0.15/5.9		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	24	20	ASTM D412 & D573
Elongation at Break (%)	600	500	ASTM D412
Force at break (N)	7	6	

#### ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
<b>Product Code</b>	93252060	93252070	93252080	93252090	93252100	93252110

#### **Performance Standards and Regulatory Compliance**







#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell,  $^{\textcircled{8}}$  and  $^{\textcircled{M}}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\textcircled{9}}$  2025 Ansell Limited. All Rights Reserved.

