

Ideal choice for aseptic controlled environments & cleanroom protection

The BioClean 2000 Cleanroom Coverall with Hood is a sterile disposable garment designed for use in aseptic controlled environment and cleanroom. The coverall is suitable for use in ISO 7 and 8 / Grade C & D cleanrooms and provides good protection for users in contact with chemicals.

- **Reduced contamination risks:** The BioClean™ 2000 features a low-linting coverall that offer good barrier protection and are less susceptible to contamination, making them ideal for cleanroom use
- **Added features:** This coverall features an integrated hood for enhanced personal protection and antistatic treated fabric
- **Optimized packaging:** All garments are provided in an individually vacuum sealed package, making them more convenient and reducing overall packaging waste



Key Features and Benefits

- **Produced and packed in NEBB certified cleanroom facility**
- **Recyclable packaging materials**
- **Sterility assurance level 10⁻⁶**
- **The coverall is specially folded to aid aseptic donning**

Industries

- Controlled and Critical Environments
- Pharmaceutical Manufacturing
- Biotechnology Manufacturing
- Medical Device Manufacturing
- Laboratory Research and Development



BioClean™ 2000 Coverall with Hood Model 111

TECHNICAL DATA SHEET

PRODUCT INFORMATION

| | |
|-----------------------------------|--|
| Material | Polyethylene/non-woven polypropylene laminate |
| Color | White |
| Audit Standards | ISO 9001:2015, Manufacturing QMS Audit Standards ISO 9001, PPE Regulation 2016 425 Module D |
| Standards | CE 0598, EN 1149-5:2018, EN ISO 13688:2013+A1:2021, EN ISO 13982-1:2004 + A1:2010, EN ISO 13982-1:2004 + A1:2010, EN 13034:2005 + A1:2009 |
| Packaging Overview | One piece per sealed inner PE bag; 25 inner bags per lined carton (25 pieces). Packed in recyclable plastic packaging and delivered in recycled cardboard shipper cases. Inner and outer bags and liner are made from polyethylene (PE) based film. Always check your local recyclable status as these materials may not be considered suitable for recycling in your location. |
| Storage | Keep away from direct sunlight; store in a dry place and keep in the original packaging. Keep away from ozone sources. If products are properly stored, as indicated, they won't lose their performances or change characteristics significantly. If products could be affected by ageing or storage, the expiry date is mentioned on the packaging materials. |
| Country Of Origin | China |
| Sterilization Method | GAMMA irradiation (25 kGy) |
| Sterilization Minimum Dose | 25kGy |
| Sterility Assurance Level | 10 ⁻⁶ |
| Cleanroom Class | ISO 7 and 8/Grade C and D |
| Shelf Life | Three (3) years from date of manufacture. |
| Construction | Bound seams with single needle stitching |
| Characteristics | *NOTE: The material is static dissipative with charge decay time of T 50 < 4 seconds. (Tested in accordance with EN 1149-3:2006) |

PARTICLE SHEDDING TEST RESULTS

| TEST | RESULT |
|--------------------------------------|--|
| Particle Shedding (Helmke Drum Test) | ≥ 0.5µm (counts/min)<12000 (Category II) |

ASTM F739-12 TEST METHOD RESULTS

| DRUG | Mean Breakthrough Time (MBT), Minutes Breakthrough of the test chemical is deemed to have occurred when the permeation rate has reached 0.1 Qg/cm ² /min |
|--------------------------|--|
| CISPLATIN | >240 |
| CARMUSTINE | <6 |
| CYCLOPHOSAMIDE | 217 (275,162,215) |
| DOXORUBICINHYDROCHLORIDE | >240 |
| 5-FLUOROURACIL | >240 |
| METHOTREXATE | >240 |
| ETOPOSIDE | >240 |
| PACLITAXEL | <10 |
| THIOTEPA | 30 (28,30,33) |

Results achieved under controlled laboratory conditions, by accredited external testing laboratory. *For Bioclean D and Bioclean 2000, the chemical permeation results relates to the fabric performance for reference only. Seams and closures may have lower breakthrough times. We recommend garments with sealed seams such as Bioclean-C to be worn over the coverall for added protection against chemotherapy drugs handling.

SIZE CHART

Size: S: Chest: 84-92cm (33"-36"), Height: 164-170cm (5'4"-5'6")
 Size: M: Chest: 92-100cm (36"-39"), Height: 170-176cm (5'6"-5'9")
 Size: L: Chest: 100-108cm (39"-42"), Height: 176-182cm (5'9"-6'0")
 Size: XL: Chest: 108-116cm (42"-45"), Height: 182-188cm (6'0"-6'2")
 Size: 2XL: Chest: 116-124cm (45"-48"), Height: 188-194cm (6'2"-6'4")
 Size: 3XL: Chest: 124-132cm (48"-51"), Height: 194-200cm (6'4"-6'6")
 Size: 4XL: Chest: 132-140cm (51"-55"), Height: 200-206 (6'6"-6'8")
 Size: 5XL: Chest: 140-148cm (55"-58"), Height: 206-212 (6'8"-7'0")



BioClean™ 2000 Coverall with Hood Model 111

MATERIAL PERFORMANCE TEST RESULTS

| TEST | RESULT | PERFORMANCE CLASS | PERFORMANCE STANDARD |
|--|----------------|-------------------|----------------------|
| Abrasion Resistance | >10 cycles | 1 | EN 12947-2 |
| Flex Cracking Resistance | >50,000 cycles | 6 | EN ISO 7854 |
| Puncture Resistance | >5 N | 1 | ISO 13996 |
| Trapezoidal Tear Resistance Cross Direction (CD) | >10 N | 1 | EN ISO 9073-4 |
| Trapezoidal Tear Resistance Machine Direction (MD) | >10 N | 1 | EN ISO 9073-4 |
| Tensile Strength Cross Direction (CD) | >30 N | 1 | EN ISO 13934-1 |
| Tensile Strength Machine Direction (MD) | >30 N | 1 | EN ISO 13934-1 |
| Repellence to Liquids - 30% H ₂ SO ₄ | >90% | 3 | ISO 6530 |
| Repellence to Liquids - 10% NaOH | >90% | 3 | ISO 6530 |
| Repellence to Liquids - O-Xylene | >90% | 3 | ISO 6530 |
| Repellence to Liquids - Butan-1-ol | >90% | 3 | ISO 6530 |
| Penetration by Liquids - 30% H ₂ SO ₄ | <1% | 3 | ISO 6530 |
| Penetration by Liquids - 10% NaOH | <1% | 3 | ISO 6530 |
| Penetration by Liquids - O-Xylene | <1% | 3 | ISO 6530 |
| Penetration by Liquids - Butan-1-ol | <1% | 3 | ISO 6530 |
| Inward leakage of aerosols of fine particles ¹ | PASS | N/A | EN ISO 13982-2 |
| Resistance to penetration by spray (Spray Test) ¹ | PASS | N/A | EN ISO 17491-4 |
| Seam Strength ² | >50 N | 2 | ISO 13935-2 |
| Electrostatic Charge Half Decay Time, t ₅₀ (secs) | PASS | N/A | EN1149-3 |

1. All interfaces with additional PPE were taped during testing, as required by the standards.
2. Seam not destroyed., 3. The material is static dissipative. Tested in accordance with EN1149-5.

ORDERING INFORMATION

| | SIZE | S | M | L | XL | 2XL | 3XL | 4XL | 5XL |
|------------------------------|-------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Coverall with Hood Model 111 | REORDER NO. | WH20-B-BC-111-02-ST1 | WH20-B-BC-111-03-ST1 | WH20-B-BC-111-04-ST1 | WH20-B-BC-111-05-ST1 | WH20-B-BC-111-06-ST1 | WH20-B-BC-111-07-ST1 | WH20-B-BC-111-08-ST1 | WH20-B-BC-111-09-ST1 |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
US T: +1 800 800 0444
US F: +1 800 800 0445
CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

UK

Ansell Nitritex
T: +44 1638 663338
F: +44 1638 668890

Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

Please see product validation pack or contact Ansell customer service for specific data on use of garments with cytotoxic drugs. Garments used for protection against such drugs must be selected specifically for the type of chemicals used.

