



BioClean™ Clearview Sterile Looped Visor Facemask VFM210-L

Sterile looped visor face mask, offering advanced bacterial and particle filtration efficiency

- **Advanced defenses:**
The BioClean™ Clearview Sterile Looped Visor Facemask VFM210-L delivers high bacterial and particle filtration efficiency, for protection of your cleanroom environment you can depend on
- **Enhanced features:** This sterile face mask features a looped design and optically clear visor, with an anti-fog coating, to enable maximized vision
- **Increased comfort:**
The BioClean™ Clearview Sterile Looped Visor Facemask VFM210-L also offers users breathable comfort

Key Features and Benefits

- **High bacterial and particle filtration efficiency:** Optimized protection
- **Anti-fog-coated visor:** Unhindered, distortion-free vision



Industries

- Controlled and Critical Environments
- Laboratory and Research
- Production and Manufacturing

Recommended For

- Biotechnologies Blending operations
- Clean room cleaning and preparing
- Medical Device Manufacturing
- Preparing pharmaceutical products
- Semiconductor manufacturing
- White goods assembly



BioClean™ Clearview Sterile Looped Visor Facemask VFM210-L

TECHNICAL DATA SHEET

PRODUCT INFORMATION

Material	Polypropylene Polyethylene
Audit Standards	Manufacturing QMS Audit Standards ISO 9001
Standards	ISO 2859, ISO 9001:2015
Packaging Overview	One piece per sealed inner PE bag; 25 inner bags per sealed outer PE bag; four outer bags per lined carton (100 pieces)
Country Of Origin	China
Sterilization Method	Gamma Irradiation
Sterilization Minimum Dose	25kGy
Sterility Assurance Level	10 ⁻⁶
Storage Instructions	Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.
Shelf Life	Five (5) years from date of manufacture

PHYSICAL PROPERTIES

Color	White
String Type	Headloop
Overall Dimensions	WIDTH (± 5mm): 210mm HEIGHT (± 5mm) : 95mm
Inner Facing Layer	Non-woven polypropylene/polyethylene (hydrophilic)
Filtration Layer	Meltblown polyester
Outer Layer	Non-woven spunbonded polyester (hydrophobic)
Fastenings	Non-latex polyurethane loops with plastic clip fastener
Noseband	Plastic coated steel

PERFORMANCE INFORMATION

Cleanroom Class	Class 10/ISO Class 4 & EU GMP Grade A/B and other sterile cleanrooms
Particle Filtration Efficiency	89.3% @0.1 micron
Bacterial Filtration Efficiency	92.3% @0.3 micron
Viral Filtration Efficiency	93.8% @3.0 micron
Differential Pressure	3.8mm H ₂ O/cm ²

ORDERING INFORMATION

	SIZE	Looped with blue clip fastener
VFM210-L	REORDER NO.	VFM210-L

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
US T: +1 800 800 0444
US F: +1 800 800 0445
CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

UK

Ansell Nitritex
T: +44 1638 663338
F: +44 1638 668890

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

