



# Our lightest\* and most comfortable glove meets ANSI/ISEA 105-2024 CUT A9 and EN ISO F measures and offers 12x greater cut resistance\*

- Enhanced comfort: 20% lighter design\* allows workers to perform varied tasks while keeping hands protected all day long
- Heightened Defenses: 12 times greater cut resistance\*\* using Next Generation single HPPE yarn developed with INTERCEPT(TM) Cut Resistance Technology for reliable hand protection
- Increased Durability: Increased Durability for Extended Use: Improved FORTIX™ Technology delivers up to 20% more abrasion resistance\*\*\* for longer lasting handling in abrasive conditions
- **Contact Heat Protection:** EN 407 contact heat level 1 to protect hands while handling hot parts

 $^{\ast}$  Versus standard ANSI/ISEA 105-2024 CUT A9 and EN ISO F rated gloves

- \*\* Versus similar gloves made of standard HPPE yarn
- \*\*\* Versus previous technology version



#### Industries

- Automotive
- Glass manufacturing
- Heavy Manufacturing
- Metal fabrication
- Machinery and Equipment
- Pulp & Paper

#### Applications

- Handling of glass sheets, sharpedged objects
- Primary assembly
- Stamping
- Machining
- Heavy Maintenance





#### **Key Features**

- The ultra-lightweight design is 20% lighter\* and meets ANSI/ISEA 105-2024 CUT A9 and EN ISO F protection standards, offering cut protection so comfortable that workers won't want to take it off.
- ANSI/ISEA 105-2024 CUT A9 and EN ISO F protection: 12x greater cut resistance\*\* for reliable hand protection.
- Improved FORTIX™ Technology: up to 20% greater durability\*\*\* .


\* Versus standard ANSI/ISEA105-2024 CUT A9 and EN ISO F

- \*\* Versus similar gloves made of standard HPPE yarn
- \*\*\* Versus previous technology version

<u>L</u>

#### **Technologies**





**Touchscreen Compatible** 

## Performance Standards & Regulatory Compliance





### **Specifications**

| BRAND   STYLE              | DESCRIPTION   | Gauge | SIZE                      | LENGTH           | COATING COLOR | PACKAGE                                       |
|----------------------------|---|-------|---------------------------|------------------|---------------|---|
| HyFlex <sup>®</sup> 11-591 | Finishing: Palm dipped, Thumbcrotch reinforcement<br>Coating Material: Nitrile<br>Liner Material: HPPE, Nylon, Spandex, Steel,<br>Graphene, Tungsten<br>Cuff Style: Knitwrist | 13    | 6, 7, 8, 9, 10,<br>11, 12 | 220mm -<br>285mm | Black         | 12 pairs/paper band, 12 paper<br>bands/carton |

For additional information visit us at www.ansell.com, or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Latin America & Caribbean Region Latin America & Carlobean Kr Ansell Commercial Mexico SA. de C.V. Blvd. Bernardo Quintana No. 7001-C, Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

North America Region Ansell Healthcare Products LLC 111 Wood Avenue South, Suite 900 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Canada Ansell Canada 105 Lauder Cowansville, QC J2K 2K8 Canada T: +1 800 363 8340 F: +1 800 267 3551

Australia Ansell Limited Level 3,678 Victoria Street, Richmond, Vic, 3121 Australia T: +61 1800 337 041 F: +61 1800 803 578

#### Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd Prima 6, Prima Avenue Block 3512, Jalan Teknokrat 6 T: +603 8310 6688 F: +603 8310 6699

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

