

## Comfortable gloves offering tactility and protection across numerous applications

- **Elevated comfort:** Ansell MICROFLEX<sup>®</sup> 92-134 Versatility disposable safety gloves are made of a soft nitrile formulation, which provides a highly comfortable fit and feel while protecting hands
- **Heightened tactility:** These nitrile disposable gloves' lightweight construction provides augmented tactile sensitivity and fine motor control
- **Optimized grip:** These MICROFLEX<sup>®</sup> gloves are textured on the fingertips to ensure a stronger grip for the safer handling of tools and materials
- **Genuine versatility:** Designed for a broad range of applications, these gloves reinforce hand protection across a wide range of industries



### Industries

- Healthcare
- Automotive
- Food Processing
- Janitorial / Sanitation
- Manufacturing
- Life Sciences
- Government

### Recommended For

- Standard patient examinations
- Picking parts and accessories
- Food processing and handling
- Catering/Meal preparation
- Disposal of waste (trash, biohazard and linens)
- Light assembly tasks
- Lab work, blending, compounding, filling, cleaning
- Preparing pharmaceutical products
- Laboratory analysis

# TECHNICAL DATA SHEET

Product Information	
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks
Packaging Overview	100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case   90 gloves per dispenser (Size XXL), 900 gloves per case (Size XXL)
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China
Product Segmentation	Standard Thin
Antistatic	No
Silicone Free	No

## PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D6319
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D6319
Finger Thickness (mm/mils)	0.11 / 4.3		ASTM D6319
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 14	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412 & D573
Force at break (N)	≥ 6	≥ 6	EN 455-2

## ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	92134060	92134070	92134080	92134090	92134100	92134110

## Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
**Ansell Healthcare Europe NV**  
 T: +32 (0) 2 528 74 00  
 F: +32 (0) 2 528 74 01

**Asia Pacific Region**  
 MY +603 8310 6688  
 apac.medical@ansell.com  
 CN: +86 21 38275000  
 infochina@ansell.com  
 JP: +813 5549 8151  
 info.medical.jp@ansell.com

**North America Region**  
**Ansell Healthcare Products LLC**  
 T: +1 800 800 0444  
 F: +1 800 800 0445

**Latin America & Caribbean Region**  
 BR +55 (11) 3356-3100  
 latam.medical@ansell.com  
 MX +52 442 296 2050  
 latam.medical@ansell.com  
 CO: +57 1 288 3247  
 latam.medical@ansell.com

**Australia**  
**Ansell Limited**  
 T: +61 1800 337 041  
 F: +61 1800 803 578

**Russia**  
**Ansell PYC**  
 Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

