

Diamond Grip Plus™ 63-754

Latex Exam Glove

Disposable latex gloves with exceptional fit and feel for extended wear

- Secure grip: MICROFLEX[®] Diamond Grip Plus[™] 63-754 disposable latex gloves are fully textured for a secure grip in both wet or dry environments
- Tactile sensitivity: Excellent tactile sensitivity ensures precise handling of delicate products or laboratory instruments
- Comfortable and elastic fit: Superior elasticity means gloves move with you for greater comfort, and are designed for easy slip-on and removal
- Outstanding quality: Exceeds standards for tensile strength, elasticity/elongation and other quality standards for average latex gloves

CAUTION: This product contains natural rubber latex, which may cause allergic reactions



Industries

- Food Processing
- Life Sciences

Recommended For

- Equipment, maintenance and repair
- All food processing, applications that have food contact
- · Sample taking and processing
- Extra comfort during long, sustained procedures



TECHNICAL DATA SHEET

| | Product Information |
|------------------------|--|
| External Glove Surface | Fully Textured |
| Audit Standards | ISO 13485, ISO 9001 |
| Packaging Overview | 100 gloves per dispenser; 10 dispensers per case; 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Product Segmentation | Multi-Purpose |
| Antistatic | Not Tested |
| Silicone Free | Yes |

PHYSICAL PROPERTIES

| | Typical | Testing Method | |
|---|---------------------|---------------------|------------------|
| Length (mm/inches) | 245 / | ASTM D3767,EN 420 | |
| Freedom from Holes (Inspection level I) | 1.5 A | ASTM D5151,EN 374-2 | |
| Palm Thickness (mm/mils) | 0.13 , | ASTM D3767,EN 420 | |
| Finger Thickness (mm/mils) | 0.16 | ASTM D3767,EN 420 | |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | 22 | 20 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 700 | ≥ 600 | ASTM D412 |
| Force at break (N) | 9 | 6 | EN 455-2 |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 63754060 | 63754070 | 63754080 | 63754090 | 63754100 |

Performance Standards and Regulatory Compliance











For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T:+32(0) 2528 7400 F:+32(0) 2528 7401 Asia Pacific Region MY+6018310 6688

Asia Pacific Region
MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

Ansell Healthcare Products LLC
T:+1800 800 0444
F:+1800 800 0445
Latin America & Caribbean Region
BR +55 (11) 3356-3100
latam.medical@ansell.com
MX:+52 442 296 2050
latam.medical@ansell.com

CO: +57 1 288 3247 latam.medical@ansell.com Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Ansell PYC Ten. +7 495 258 13 16

Ansell, ® and ¬¬ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

