

Nitrile disposable gloves with excellent dexterity, along with enhanced comfort, fit and feel

- **ERGOFORM[®] Technology:** ERGOFORM[™] Design Technology reduces muscle strain during repetitive tasks, improving worker comfort and productivity
- **Black nitrile composition:** Distinctive black color provides contrast while also hiding the appearance of oils, dirt and grime
- **Secure grip:** Textured on the fingertips for a reliable consistent grip, ensuring tactility and secure handling of instruments and materials
- **Comfort and dexterity:** MICROFLEX[®] Touch 93-7321 nitrile disposable gloves provide excellent dexterity along with enhanced comfort, fit and feel



Industries

- Automotive
- Automotive Aftermarket
- Chemical
- Correctional Facilities
- Life Sciences
- Machinery and Equipment
- Maintenance
- Manufacturing

Recommended For

- Inspection, selecting, checking parts
- Laboratory analysis
- Paint shop
- Oil, fluids and filter change
- General Purpose Auto Aftermarket
- Equipment repair and maintenance

TECHNICAL DATA SHEET

Product Information	
External Glove Surface	Textured Fingers
Audit Standards	21 CFR 820, ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks
Packaging Overview	100 gloves per box; 10 boxes per case; 2XL 90 gloves per box; 900 gloves per carton
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China
Product Segmentation	High Touch
Antistatic	No
Silicone Free	No


PHYSICAL PROPERTIES

	Typical Values	Testing Method	
Length (mm/inches)	245 / 9.6	ASTM D6319, EN 455-2	
Freedom from Holes (Inspection level I)	1.5 AQL	ASTM D5151, EN 455-1	
Palm Thickness (mm/mils)	0.07 / 2.8	ASTM D6319, EN 455-2	
Finger Thickness (mm/mils)	0.11 / 4.3	ASTM D6319, EN 455-2	
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 16	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412 & D573
Force at break (N)	≥ 6	≥ 6	EN 455

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XS (5.5 - 6)	XXL (10.5 - 11)
Product Code	937321070	937321080	937321090	937321100	937321060	937321110

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
 Ansell Healthcare Europe NV
 T: +32 (0) 2 528 74 00
 F: +32 (0) 2 528 74 01

Asia Pacific Region
 MY +603 8310 6688
 apac.medical@ansell.com
 CN: +86 21 38275000
 infochina@ansell.com
 JP: +813 5549 8151
 info.medical.jp@ansell.com

North America Region
 Ansell Healthcare Products LLC
 T: +1 800 800 0444
 F: +1 800 800 0445

Latin America & Caribbean Region
 BR +55 (11) 3356-3100
 latam.medical@ansell.com
 MX: +52 442 296 2050
 latam.medical@ansell.com
 CO: +57 1 288 3247
 latam.medical@ansell.com

Australia
 Ansell Limited
 T: +61 1800 337 041
 F: +61 1800 803 578

Russia
 Ansell PYC
 Ten. +7 495 258 13 16

Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

