

55-105 Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

NRL RABS/isolator gloves, with certified tear and abrasion resistance

Port size: 203mm/8"
Thickness: 0.76mm/30 mil

 Sustained protection: AlphaTec® NRL RABS and Isolator Gloves 55-105 satisfy EN 388 standards for Level 2 tear and abrasion resistance

 Improved durability: Heavyweight thickness means they boast enhanced durability, for longer-lasting wear

 Limited contamination risks: These RABS gloves are susceptible to fewer contamination risks and easy to keep clean, thanks to their unlined and translucent design

KEY FEATURES & BENEFITS

- EN 388 compliance: For tear- and abrasion-resistant safety gloves
- **Heavyweight thickness:** Enhanced durability, for longer glove life
- Unlined: Fewer contamination risks and easier cleaning







55-105

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

TECHNICAL DATA SHEET

| Product Reference | 55-105 |
|------------------------|--|
| Material | Natural Rubber Latex |
| Color | Natural |
| Shape | Ambidextrous |
| External Glove Surface | Smooth |
| Cuff Style | Beaded |
| Storage Instructions | Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use. |
| Available Sizes | 10 |
| Temperature Range | From -30°C to 50°C |
| Shelf Life | Three (3) years from date of manufacture. |
| Standards | CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-1:2016, EN ISO 374-5:2016, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 388:2016, EN 420:2003 + A1:2009, Category III |





55-105

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

PHYSICAL PROPERTIES

| | Typical Values | Testing Method |
|---|------------------|----------------|
| Typical Length (mm/in) | 813 mm / 32" | EN 455-2 |
| Port Size | 203mm/8" | |
| | | |
| | | |
| Target Single Wall Palm Thickness (mm/mil) | 0.76 mm / 30 mil | EN 455-2 |
| Target Single Wall Cuff Thickness (mm/mil) | 0.76 mm / 30 mil | EN 455-2 |

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

| Risk | Performance level |
|----------------------|-------------------|
| Abrasion Resistance | Level 2 |
| Blade Cut Resistance | Level 1 |
| Tear Resistance | Level 2 |
| Puncture Resistance | Level 1 |

ORDERING INFORMATION

| | PORT SIZE | 8"/203mm |
|--------|-------------|----------|
| | SIZE | 10 |
| 55-105 | REORDER NO. | 55105100 |

Performance Standards and Regulatory Compliance

C € 0493







For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890







Ansell, $^{\textcircled{8}}$ and $^{\textcircled{m}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{c}}$ 2024 Ansell Limited. All Rights Reserved.

