

# NeoTouch™ 25-201

Disposable Neoprene Glove with Extended Cuff

# Extended, chemical-resistant disposable neoprene gloves, with superb wet and dry grip performance

- Specialized protection: Provides strong chemical splash protection from most acids and alcohols and EN 374 Type B chemical resistance certification
- Strong grip: Textured fingertips and neoprene material enhance grip performance in wet and dry environments
- Reduced allergy risk: Non-latex formulation prevents Type 1 (latex) allergic reactions
- Easy donning: Polymer-coated, these MICROFLEX® gloves are easy to don
- Extended protection: MICROFLEX<sup>®</sup>
  NeoTouch™ 25-201 gloves' extended
  cuff also provides greater forearm and
  wrist protection



## **Industries**

- Life Sciences
- Chemical

#### **Recommended For**

- Transferring liquids and solids
- Sample taking and processing
- Testing



# **TECHNICAL DATA SHEET**

|                             | Product Information  |
|-----------------------------|--|
| External Glove Surface      | Textured Fingers   |
| Audit Standards             | ISO 13485  |
| Packaging Overview          | 100 gloves per dispenser<br>10 dispensers per case<br>1000 gloves per case                               |
| Storage Instructions        | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin           | Indonesia  |
| <b>Product Segmentation</b> | High Risk  |
| Antistatic                  | Yes EN1149   |
| Silicone Free               | No   |

### **PHYSICAL PROPERTIES**

|   | Typical             | Testing Method |                     |
|---|---------------------|----------------|---------------------|
| Length (mm/inches)                      | 285 / 11.2          |                | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 1.5 AQL             |                | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.13 / 5.1          |                | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.16 / 6.3          |                | ASTM D3767,EN 420   |
|   | <b>BEFORE AGING</b> | AFTER AGING    |                     |
| Ultimate Tensile Strength (MPa)         | ≥ 14                | ≥ 18           | ASTM D412 & D573    |
| Elongation at Break (%)                 | ≥ 700               | ≥ 600          | ASTM D412           |
| Force at break (N)                      | ≥ 3.6               | ≥ 3.6          |                     |

### **ORDERING INFORMATION**

| Size         | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|-------------|-------------|-------------|---------------|
| Product Code | 25201070    | 25201080    | 25201090    | 25201100      |

### **Performance Standards and Regulatory Compliance**













# For additional information visit us at www.ansell.com, or call us at

**Europe, Middle East & Africa Region** Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region
MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info medical in@ansell.com

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell,  $^{\textcircled{8}}$  and  $^{\textcircled{M}}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\textcircled{C}}$  2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

