

Validated sterile nitrile RABS/isolator sleeves with low particle levels and superb ESD properties

- **Assured quality:** The BioClean™ Sterile Nitrile RABS/Isolator Sleeve GSL20NITPP26 is 100% visually inspected and triple bagged to ensure high-quality protection
- **Increased versatility:** These isolator sleeves are compatible with autoclaving, VHP and IPA, enabling the use of three sterilization methods
- **Improved practicality:** In addition, the BioClean™ Sterile Nitrile RABS/Isolator Sleeve GSL20NITPP26 are compatible with a broad range of cuff systems
- **Enhanced features:** They also have extremely low particulate levels and excellent ESD properties



KEY FEATURES & BENEFITS

- **Triple bagged and 100% visually inspected:** High-quality arm protection
- **Versatile RABS/Isolator sleeves:** Compatible with a variety of cuff systems
- **Autoclave compatibility:** Withstands pressurized, high-temperature conditions

Industries

- Pharmaceutical Manufacturing
- Laboratory Research and Development
- Raw Material and Preparation
- Biotechnology Manufacturing
- Sterile Processing Department
- Semiconductor manufacturing



GSL20NITPP26

Validated Sterile Nitrile RABS / Isolator Sleeve

TECHNICAL DATA SHEET

| | |
|------------------------|---|
| Product Reference | GSL20NITPP26 |
| Material | Nitrile |
| Color | White |
| External Glove Surface | Smooth |
| Cuff Style | Beaded |
| Audit Standards | ISO 14001, ISO 9001:2008, NEBB Certified Cleanrooms |
| Packaging Overview | One piece per sealed inner PE bag; one inner bag per sealed second inner PE bag; one second inner bag per sealed outer PE bag; 20 outer bags per lined inner white Correx polyethylene box (20 pieces). |
| Storage Instructions | Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light. |
| Country Of Origin | Malaysia |
| Temperature Range | From -10°C to 120°C |
| Sterilization Method | GAMMA irradiation (25 kGy) |
| Cleanroom Class | Class 10/ISO 4 & EU GMP Grade A |
| Shelf Life | Three (3) years from date of manufacture. |
| Protein Level | N/A: contains no natural rubber latex |
| Antistatic | Yes |
| Standards | Category III, CE 0493, EC 1935/2004, ISO 11137-1:2006, EN 388:2016 +A1:2018, EN 420:2003 + A1:2009, EN 455 Part 2, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 421:2010 |



GSL20NITPP26

Validated Sterile Nitrile RABS / Isolator Sleeve

PHYSICAL PROPERTIES

| | Typical Values | Testing Method |
|--|----------------|----------------|
| Typical Length (mm/in) | 660/26 | EN ISO 21420 |
| Port Size | 8" | |
| Target Single Wall Cuff Thickness (mm/mil) | 0.50/20 | EN 455-2 |

ORDERING INFORMATION

| | PORT SIZE | 8"/203mm |
|--------------|-------------|--------------|
| | SIZE | 8"/203mm |
| GSL20NITPP26 | REORDER NO. | GSL20NITPP26 |

Technology



NO RUBBER LATEX

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
US T: +1 800 800 0444
US F: +1 800 800 0445
CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

UK

Ansell Nitritex
T: +44 1638 663338
F: +44 1638 668890



EN ISO 374-1:2016

EN ISO 374-5

VIRUS

EN 421

AJKNOTS

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

