



BioClean™ Non-sterile Looped Facemask MEA210-0

Non-sterile, looped face mask with advanced filtration efficiency (bulk-packed)

- **Advanced defenses:** The BioClean™ Non-sterile Looped Face Mask MEA210-0 delivers high bacterial, viral and particle filtration efficiency, while offering greater breathability and comfort for the user
- **Enhanced features:** This looped non-sterile face mask can be equipped with a clip connector (clip to purchase separately – CC-FMC4), which facilitates quick and secure fastening at the back of the head
- **Reduced contamination risks:** This cleanroom face mask is processed in a NEBB-certified ISO Class 4 cleanroom environment for reduced contamination risks and personal protection you can depend on



Key Features and Benefits

- **Contamination control:** High particle and Bacterial Filtration Efficiency (BFE)
- **Cleanroom-compatible materials:** Less contamination risks
- **Clip connector:** For easy and secure fastening

Industries

- Production and Manufacturing
- Controlled and Critical Environments
- Laboratory and Research



BioClean™ Non-sterile Looped Facemask MEA210-0

TECHNICAL DATA SHEET

PRODUCT INFORMATION

Material	Polypropylene Polyethylene
Audit Standards	Manufacturing QMS Audit Standards ISO 9001
Standards	ASTM F2101, ISO 2859, ISO 9001:2015
Packaging Overview	MEA 210-0 (Bulk): 100 pieces per sealed inner PE bag; one inner bag per sealed outer PE bag; 20 outer bags per lined carton (2000 pieces) CC-FMC4 (Blue clip connector - sold separately): 500 clips per sealed inner PE bag; four inner bags per sealed outer PE bag; 10 outer bags per lined carton (20,000 pieces)
Country Of Origin	China
Storage Instructions	Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.
Shelf Life	Five (5) years from date of manufacture.

PHYSICAL PROPERTIES

Color	White
String Type	Headloop
Overall Dimensions	WIDTH (± 5mm) 210mm HEIGHT (± 5mm) 95mm
Inner Facing Layer	Non-woven polypropylene/polyethylene (hygroscopic)
Filtration Layer	Meltblown polypropylene
Outer Layer	Non-woven polypropylene polyethylene hydrophobic
Fastenings	Non-latex polyurethane loops
Noseband	Plastic coated steel

PERFORMANCE INFORMATION

Cleanroom Class	Class 10/ISO 4
Particle Filtration Efficiency	99.9% @0.1 micron
Bacterial Filtration Efficiency	>99.9% @0.3 micron
Viral Filtration Efficiency	99.8% @3.0 micron
Differential Pressure	6.9mm H ₂ O/cm ²

ORDERING INFORMATION

	SIZE	Clip Connector	Bulk Packing
MEA210-0	REORDER NO.	CC-FMC4	MEA210-0

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
US T: +1 800 800 0444
US F: +1 800 800 0445
CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

UK

Ansell Nitritex
T: +44 1638 663338
F: +44 1638 668890

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

