

93-360 Non-sterile Disposable Nitrile & Neoprene (Polychloroprene) Cleanroom Glove

Extra-thin chemical-resistant cleanroom gloves, featuring a robust, tactile three-layer design

- Specialized protection: MICROFLEX® 93-360 antistatic cleanroom gloves feature a three-layer design, offering superb protection from harsh chemicals, including acids, bases and various solvents
- Elevated comfort: Their extra-soft proprietary formulation combines comfort, tactility and dexterity
- Reduced allergy risks: These siliconefree cleanroom gloves' nitrile and neoprene composite is free of latex, preventing the risk of Type I latex allergies
- Minimized contamination risks: As these MICROFLEX® gloves come in nonparticulating EasyTear packaging, potential contamination risks are also kept to a minimum

KEY FEATURES & BENEFITS

- Three-layer design: Protection against harsh chemical hazards*
- **Proprietary formulation:** Comfort, tactility and dexterity
- Nitrile and neoprene composite: Type I latex allergy risks eliminated

*including acids, solvents and bases

Industries

- Pharmaceutical Manufacturing
- Biotechnology Manufacturing
- Medical Device Manufacturing
- Electronics manufacturing

Recommended For

- Clean room cleaning and preparing
- Blending, compounding solids and liquids
 - Spill or leakage cleanup
 - Transferring liquids and solids
 - Loading centrifuges and chromatography columns
 - Assembly of parts
 - Weighing and dispensing of solid and liquid raw materials







93-360 Non-sterile Disposable Nitrile & Neoprene (Polychloroprene) Cleanroom Glove

TECHNICAL DATA SHEET

	Product Information		
Matarial			
Material	Nitrile and Neoprene (Polychloroprene)		
Color	Teal, Blue		
Shape	Ambidextrous		
Cuff	Beaded		
Manufacturing/QMS Audit Standards	ISO 9001		
Regulatory/Standard Compliance	ASTM D6319, CE 0493, EN 388:2016, EN 421:2010, EN ISO 21420:2020, EN ISO 374-1:2016, EN ISO 374-5:2016, UKCA		
	50 gloves packed in a vacuum-sealed polybag. 1 bag of 50 gloves per master polybag. 10 master polybags inside a poly case liner placed inside a shipper/carton. In total 500 gloves per carton.		
Packaging	More sustainable packaging: These nitrile and neoprene gloves are packed in recyclable plastic packaging* and delivered in recycled cardboard shipper cases. *Inner wrap, pouch, bag and liner are made from polyethylene (PE) based film. Always check your local recyclable status as these materials may not be considered suitable for recycling in your location.		
Storage	Keep away from direct sunlight; store in a dry place and keep in the original packaging. Keep away from ozone sources. If products are properly stored, as indicated, they won't lose their performances or change characteristics significantly. If products could be affected by ageing or storage, the expiry date is mentioned on the packaging materials.		
Country of Origin	Sri Lanka		
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10), 2XL (10.5-11)		
Powder Content	Powder-Free		
External Glove Surface	Textured Fingers		
Internal Glove Surface	Chlorinated		
Cleanroom Class	Class 100/ISO 5		
Shelf Life	5 years		
Tested for use with Chemotherapy Drugs	Yes, in accordance with ASTM D6978 (Not listed in the US FDA 510k)		
Protein Level	N/A: contains no natural rubber latex		
Anti-static	Yes		
Vulcanization Chemical Accelerators	• Zinc Dibutyldithiocarbamate (ZDBC) Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.		





93-360

Non-sterile Disposable Nitrile & Neoprene (Polychloroprene) Cleanroom Glove

Physical Properties							Testing Method
Sizes	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	2XL (10.5-11)	
Typical Length (mm/in)		≥ 285 / 11.2					EN 420,ASTM D3767
Palm Width (mm/in)	76/3.0	85/3.4	95/3.7	106/4.2	115/4.5	122/4.8	
Freedom from Holes		0.65 AQL / Performance Level 3					ASTM D6319-10,ASTM D5151-06 (2011)
Target Single Wall Palm Thickness (mm/mil)	0.20 / 7.9					EN 420,ASTM D3767	
Target Single Wall Finger Thickness (mm/mil)		0.23 / 9.1					EN 420/ASTM D3767
Target Single Wall Cuff Thickness (mm/mil)		0.15 / 5.9					EN 420/ASTM D3767
Ultimate tensile strength (MPa) During Aging	Min. 16					ASTM D412-06a	
Force at Break (N) During Aging	≥6					EN 455-2	

IONIC CONTENT

Concentration in µg/cm ²	Typical	Concentration in µg/cm ²	Typical
Ammonium	<0.06	Nitrate	<1.00
Bromide	<0.01	Nitrite	<0.0004
Calcium	<1.25	Phosphate	<0.0004
Chloride	<0.65	Potassium	<0.08
Fluoride	<0.01	Sodium	<0.13
Lithium	<0.0004	Sulphate	<0.15
Magnesium	<0.05	Zinc	<0.03

ORDERING INFORMATION

SIZE	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	2XL (10.5-11)
REORDER NO.	93360060	93360070	93360080	93360090	93360100	93360110

PERFORMANCE STANDARDS AND REGULATORY COMPLIANCE



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

