MICROFLEX™

Mega Texture 93-256

Orange Short Cuff Nitrile Disposable Glove with Raised Grip

Nitrile disposable gloves that provide confident grip and durable protection

- **Enhanced grip:** Featuring our Mega Texture surface for consistent grip in wet and dry conditions
- **Tear resistance:** Robust 0.13mm/5.1mil palm thickness to resist tearing in use
- **High visibility:** Orange color to increase visibility while working
- **Durable:** Strong formulation providing durable yet comfortable hand protection
- **Food approved:** Ideal for a wide range of food handling applications



Industries

- Automotive
- Automotive Aftermarket
- Construction
- Machinery and Equipment
- Maintenance
- Manufacturing
- Recycling and Waste Disposal

Recommended For

- General Purpose Auto Aftermarket
- Tire rotation & changes
- Vehicle maintenance
- Food processing and handling
- Oil, fluids and filter change
- Mechanical jobs
- Engine transmission and repair
- Maintenance
- Assembly of parts

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Arrette du 05/08/2020, EU Food Contact Approved, EC 2023/2006, ASTM D6319, CE 0493, EN ISO 21420:2020, EN ISO 374-1:2016+A1:2018 Type B JKPT, EN ISO 374-5:2016, FDA21 CFR 177-2600-US Food Contact Approved, ISO 13485, ISO 9001, ISO 18889:2019 G1, UKCA, EN 1149
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Thailand
Product Segmentation	Robust
Antistatic	Yes EN1149
Silicone Free	Yes
Vulcanization Chemical Accelerators	• Zinc Dibutyldithiocarbamate (ZDBC) *Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.*

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.45		ASTM D6319,ASTM D3767
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1,EN 374-2
Palm Thickness (mm/mils)	0.13/5.1		ASTM D6319,ASTM D3767
Finger Thickness (mm/mils)	0.16/6.3		ASTM D6319,ASTM D3767
	BEFORE AGING	**AFTER AGING**	
Elongation at Break (%)	≥500	≥400	ASTM D412 & D573
Force at break (N)	≥6	≥6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	93256070	93256080	93256090	93256100	93256110

Performance Standards and Regulatory Compliance

CE 0493 · EN ISO 374-1:2016 Type B JKPT · EN ISO 374-5 VIRUS · ISO 13485 · ISO 9001 · G1 ISO 18889 · UK CA

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

Ansell