

Lightweight, comfortable and durable hand protection with light chemical splash protection

- Comfort and durability: Lightweight TouchNTuff[®] 92-616 gloves offer durability with a soft feel
- Reliable chemical protection: These gloves provide good splash resistance against hydrocarbons, fats, grease and alcohols
- Food handling compliance: TouchNTuff[®] 92-616 are ideally suited for a wide range of food processing tasks
- Reduced allergy risk: Nitrile formulation prevents Type 1 (latex) allergic reactions
- Smart packaging: Packaged with 150 gloves per dispenser to minimize waste



Industries

• Food Processing

Recommended For

• All food processing, applications that have food contact



TECHNICAL DATA SHEET

| | Product Information |
|------------------------|----------------------------------------------------------------------------------------------------------|
| External Glove Surface | Textured Fingers |
| Audit Standards | ISO 13485, ISO 9001 |
| Packaging Overview | 150 gloves per dispenser 10 dispensers per case 1500 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Product Segmentation | Standard Thin |
| Antistatic | Not Tested |
| Silicone Free | No |

PHYSICAL PROPERTIES

| | Typical | Testing Method | |
|-----------------------------------------|--------------|---------------------|-------------------|
| Length (mm/inches) | 240 / | ASTM D3767,EN 420 | |
| Freedom from Holes (Inspection level I) | 1.5 A | ASTM D5151,EN 455-1 | |
| Palm Thickness (mm/mils) | 0.08 | /3.1 | ASTM D3767,EN 420 |
| Finger Thickness (mm/mils) | 0.15/5.9 | | ASTM D3767,EN 420 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | ≥ 14 | ≥ 14 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 500 | ≥ 400 | ASTM D412 |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 92616XS | 9261600S | 9261600M | 9261600L | 92616XL |

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at North America Region

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000

infochina@ansell.cor JP: +813 5549 8151 ansell.com al.jp@ansell.com info.m

Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445 Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050

latam.medical@ansell. CO: +57 1 288 3247 latam.medical@ansell.

Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

ell.com

ell.com

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

