

## Chemical-resistant disposable gloves that deliver durable protection and superior comfort.

- **Three-layer design:** Three layers ensure superior protection against harsh chemicals
- **Tactility:** Designed to be thinner than standard reusable chemical-resistant gloves, providing protection while allowing for better tactility when handling small objects and tools
- **Elevated comfort:** Soft material and ergonomic design offer outstanding fit, feel and flexibility
- **Assured quality:** Their low AQL (0.65) means minimal pinhole defect risks
- **High standards:** Meets EN 374 Type A certified in Europe and KOSHA certified in Korea
- **Retail pack:** Available in convenient packaging of 6 gloves, size specific



### Industries

- Aerospace
- Automotive
- Automotive Aftermarket
- Life Sciences
- Agriculture
- Infrastructure Maintenance
- Chemical

### Recommended For

- General Purpose Auto Aftermarket
- Production line support and maintenance
- Sample taking and processing
- Transferring liquids and solids between vessels and tanks and process equipment
- Oil, fluids and filter change
- Inspection, selecting, checking parts
- Assembly and inspection of components
- Equipment repair and maintenance
- Blending, compounding solids and liquids

# TECHNICAL DATA SHEET

Product Information	
<b>Material</b>	Nitrile, Neoprene
<b>External Glove Surface</b>	Textured Fingers
<b>Audit Standards</b>	ISO 9001
<b>Product Certification</b>	Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, EN 388:2016 2000X, CE 0493, EN 421:2010, EN ISO 21420:2020, EN ISO 374-1:2016 Type A JKLOPST, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, ISO 18889:2019, ISO 9001, DOSH-SIRIM certified, Kosha certified, UKCA
<b>Packaging Overview</b>	50 gloves per dispenser 10 dispensers per case 500 gloves per case  Retail Pack: 6 gloves per pack; 50 packs per case; 300 gloves per case
<b>Storage Instructions</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country Of Origin</b>	Sri Lanka
<b>Product Segmentation</b>	High Risk
<b>Antistatic</b>	Yes EN1149
<b>Fentanyl Tested</b>	Yes
<b>Silicone Free</b>	Yes

## PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	≥ 285 / 11.2		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.20/7.9		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.20/7.9		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	<b>AFTER AGING</b>	
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 6	≥ 6	EN 455-2

## ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	93260060	93260070	93260080	93260090	93260100	93260110	93260RP080	93260RP090	93260RP100	93260RP110
Retail Pack Catalog No.			93260RP080	93260RP090	93260RP100		93260RP080	93260RP090	93260RP100	

### Performance Standards and Regulatory Compliance



### For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### Asia Pacific Region

MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

#### North America Region

Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Latin America & Caribbean Region

BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

#### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Russia

Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

