

Previously known as: TRELLCHEM® Splash 900

Reusable, rear-entry full-body splash protection suit, offering a liquid-tight barrier.

- **Advanced defenses:** The AlphaTec® 66-330 Model 156-G09 reusable protective suit features rear-entry full-body splash protection
- **Improved comfort and safety:** As this anti-static suit is composed of a strong, soft and flexible fabric, it grants optimal comfort and personal protection
- **Enhanced protection:** In addition, this greenish-yellow hazmat suit shields against harmful chemicals, such as alkalis, acids and hazardous infective agents
- **Certified performance:** The AlphaTec® 66-330 Model 156-G09 hazmat splash suit complies with EN 14605:2005, Type 3 (liquid-tight) requirements



Industries

- Chemical
- Industrial
- Fire and Rescue

Applications

- Chemical Handling
- Fire & Rescue
- First Responders
- Emergency Teams
- Hazmat Teams
- Industrial and Tank Cleaning
- Petrochemicals

KEY FEATURES & BENEFITS

- **Rear-entry full-body splash protective suit:** Cost-effective hazmat PPE
- **Strong, flexible and anti-static fabric:** Comfort and safety assured
- **Good chemical and biological barrier:** Reliable PPE protective suit


Material Diagram



Seam Diagram



Performance Standards



Product Information

| Product Information | |
|---------------------|--|
| Available Sizes | 2XS, XS, S, M, L, XL, 2XL, 3XL |
| Color | Orange |
| Country Of Origin | Lithuania |
| Models Available | 151-G09, 156-G09 |
| Packaging Overview | Individually Packed |
| Product Material | Strong and flexible polyester fabric, coated with PVC on both sides. |
| Product Reference | 66-330 Model 156-G09 |
| Standards Overview | <ul style="list-style-type: none">• EN 14605:2005 + A1:2009, type 3 (liquid-tight)• EN 14126:2003 (infective agent protection)• EN 1149-5:2008 (anti-static suit material) |
| Seam Type | Double welded |
| Shelf Life | 7 years |

Suit components & accessories

| Suit Components and Accessories | |
|------------------------------------|---|
| Design Features | <ul style="list-style-type: none"> • Anatomically designed face seal for optimum safety and comfort • Sewn-in socks • Watertight PVC zipper • Knees and elbows are reinforced to provide extra abrasion resistance • Bayonet glove ring system for quick and simple glove exchange |
| Visor And Face Seal | Anatomically designed rubber face seal. |
| Gloves And Attachments | AlphaTec® 08-354 gloves. The gloves are attached with a Bayonet glove ring system, which offers quick and simple glove exchange. |
| Footwear And Attachments | Sewn-in socks, for use with separate boots (Model 156). Boots are not included but available to order. |
| Zipper | Rear-entry watertight PVC zipper. The zipper is placed horizontally across the shoulders for ease of donning, and is protected by a splash guard/flap with hook-and-loop closure. |
| Ventilation | Fitted with an AlphaTec® Exhaust valve on the chest, to ventilate excess air inside the suit. |
| Included With Each Delivery | • 2 pcs extra locking pins for the Bayonet glove ring system • 1 pce Molycote lubrication for the O-rings in the Bayonet glove ring system • 1 pce grease stick for lubrication of the zipper |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444

Australia
Ansell Limited
T: +61 1800 337 041

Asia Pacific Region
Ansell Global Trading Center
T: +603 8310 6688

Latin America & Caribbean Region
Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

