

## Sterile single-use goggles, featuring enhanced anti-fog coating capabilities

- **Assured protection:** BioClean™ Clearview Goggles BCGS1 meet ANSI/ISEA and EN standards, providing reliable certified eye protection.
- **Reduced contamination risks:** The indirect ventilation system minimizes contamination risks when entering controlled environments
- **Enhanced features:** These anti-fog goggles feature an optically correct, toughened polycarbonate lens with an anti-scratch and anti-fog coating, which lessens distortion and ensures clear vision
- **Increased comfort:** BioClean™ Clearview Goggles BCGS1 are composed of lightweight ultra-soft PVC with a non-linting, latex-free headband, meaning they are ideal when worn over eyeglasses



### Key Features and Benefits

- **ANSI / ISEA compliance:** Certified personal eye protection
- **Indirect ventilation system:** Minimized contamination risks
- **Anti-scratch and anti-fog properties:** For clear, unobstructed vision

### Industries

- Controlled and Critical Environments
- Production and Manufacturing
- Laboratory and Research

### Recommended For

- Clean room cleaning and preparing
- Chemical Handling
- Blending, compounding solids and liquids
- Pharmaceutical manufacturing
- Preventing the risk of cross-contamination
- Testing
- Transferring liquids and solids between vessels and tanks and process equipment
- Semiconductor manufacturing
- Medical Device Manufacturing
- Preparing pharmaceutical products



# BioClean™ Clearview Goggles BCGS1

## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

Material	PVC, Polycarbonate, Silicone
Color	Clear
Audit Standards	Manufacturing QMS Audit Standards ISO 9001, PPE Regulation 2016 425 Module D
Standards	CE Number, EN 166:2001, ISO 9001:2015, Category II, UKCA
Packaging Overview	One piece per sealed Tyvek™/PE inner bag; 10 inner bags per sealed outer bag; six outer bags per lined carton (60 pieces)
Sterilization Method	Ethylene Oxide (EtO)
Cleanroom Class	Class 10/ISO Class 4 & EU GMP Grade A/B and other sterile cleanrooms
Shelf Life	Three (3) years from date of manufacture.
Classification	EN166
Optical Class	1
Storage Instructions	Keep away from direct sunlight; store in a dry place and keep in the original packaging. Keep away from ozone sources. If products are properly stored, as indicated, they won't lose their performances or change characteristics significantly. If products could be affected by ageing or storage, the expiry date is mentioned on the packaging materials.
Weight	74g

### PHYSICAL PROPERTIES

Overall Dimensions	Total Weight (± 2g): 74g Lens Thickness (±0.3mm): 2mm Bridge Width (±0.5mm): 50mm Bridge Height (±0.5mm): 25mm Overall Width (hinge to hinge)(±3mm): 155mm Overall Height (±3mm): 85mm
--------------------	--

### ORDERING INFORMATION

	SIZE	Universal
BCGS1	REORDER NO.	BCGS1



# BioClean™ Clearview Goggles BCGS1

## EXPLANATION OF FRAME MARKINGS

Required Markings	Markings On Frame	Meaning
Manufacturers Identification Mark	Ansell	Ansell
Brand	BioClean	BioClean™
Standard Number	EN166	European Standard on Personal Eye Protection
Field of Use	3	Liquids (droplets or splashes)
Field of Use	4	Large dust particles (Dust with a particle size > 5 µm)
Field of Use	B	Medium energy impact
Conformity Mark	CE	Conformity with European Standards
Conformity Mark - Meaning	(ANSI) Z87.1	American National Standard for Occupational and Educational Personal Eye and Face Protection Devices. Protection against flying fragments, objects, large chips, particles, sand, dirt etc.
Field of Use	Z87+	High impact rating
Field of Use	D3	Splash and Droplet
Field of Use	D4	Dust
Field of Use	UKCA	Conformity with Great Britain Standard

## EXPLANATION OF OCULAR MARKINGS

Required Markings	Markings On Ocular	Meaning
Scale Number For Filter	2C-1.2	UV with good color recognition; Clear lens
Manufacturers Identification Mark	BioClean	BioClean™
Optical Class	1	High optical quality
Mechanical Strength	B	Medium energy impact
Field of Use	O	Original Ocular
Original Or Replacement Ocular	O	Original ocular
Conformity Mark - Meaning	(ANSI) Z87.1	American National Standard for Occupational and Educational Personal Eye and Face Protection Devices. Protection against flying fragments, objects, large chips, particles, sand, dirt etc.
UV Filter Transmittance	U6	Max Effective Far UV= .01% / Max Near UV= .1% (block out 99.9% of UV light)

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

### Asia Pacific Region

Ansell Global Trading Center  
T: +603 8310 6688  
F: +603 8310 6699

### North America Region

Ansell Healthcare Products LLC  
US T: +1 800 800 0444  
US F: +1 800 800 0445  
CA T: +1-800-363-8340

### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
T: +52 442 248 1544 / 248 3133

### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

### UK

Ansell Nitritex  
T: +44 1638 663338  
F: +44 1638 668890

## Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

