

BioClean-D™ Dropdown Sterile Coverall with Hood S-BDSH

Sterile drop-down cleanroom coverall, featuring removable tabs for aseptic donning

- Enhanced features: The BioClean-D
 Drop-down Sterile Garment with Hood
 S-BDSH boasts drop-down design
 technology, preventing needless
 external surface contact, and is
 equipped with quick-release tabs and
 internal colored tabs, indicating safe
 touch points that further ensure aseptic
 donning
- Reduced contamination risks: This antistatic garment is manufactured from low-linting CleanTough™ material, which reduces particle contamination risks
- Optimized fit: This disposable cleanroom garment is also equipped with an elasticated back, hood, cuffs and ankles, with thumb loops to ensure a secure hold and fit

Key Features and Benefits

- Drop-down design* technology: Aseptic donning made easy
- CleanTough™ fabric: For an antistatic, low-linting sterile garment
- Quick-release press stud tabs: Aseptic donning further facilitated

Patent #US8683615, US9532614B2



Industries

- Controlled and Critical Environments
- Production and Manufacturing
- Pharmaceutical Manufacturing
- Biotechnology ManufacturingMedical Device Manufacturing
- Laboratory and Research







BioClean-D™ Dropdown Sterile Coverall with Hood S-BDSH

TECHNICAL DATA SHEET

PRODUCT INFORMATION

Material	CleanTough™
Audit Standards	ISO 14001, Manufacturing QMS Audit Standards ISO 9001, PPE Regulation 2016 425 Module D, NEBB Certified Cleanrooms
Standards	ASTM F739, ISO 11137-1:2006, EN 13934-1, EN 13935-2, EN 6530, EN 7854, EN 863, EN 9073-4, EN ISO 13688:2013
Packaging Overview	One piece aseptically folded per sealed inner PE bag; one inner bag per sealed outer PE bag; 20 outer bags per lined carton (20 pieces). Please note: sizes 3XL, 4XL, 5XL, 6XL, 7XL & 8XL 15 coveralls per carton.
Storage	Store in a dry cool place 40°C away from direct sunlight and fluorescent light.
Country Of Origin	Sri Lanka
Sterilization Method	GAMMA irradiation (25 kGy)
Sterilization Minimum Dose	25kGy
Sterility Assurance Level	10-6
Cleanroom Class	Class 10/ISO Class 4 & EU GMP Grade A/B and other sterile cleanrooms
Shelf Life	5 years from date of manufacture
Construction	Bound seams with single needle stitching
Characteristics	*NOTE: BioClean CleanTough material is static dissipative and, with a charge half decay time of 0.07 sec, and so are ideal for use in a static-safe environment.

PARTICLE SHEDDING TEST RESULTS

TEST	RESULT	
Particle Shedding (Helmke Drum Test)	≥ 0.5Qm (counts/min) <2000	

ASTM F739-12 TEST METHOD RESULTS

DRUG	Mean Breakthrough Time (MBT), Minutes Breakthrough of the test chemical is deemed to have occurred when the permeation rate has reached 0.1 Qg/cm² /min
CISPLATIN	>240
CARMUSTINE	<6
CYCLOPHOSHAMIDE	217 (275,162,215)
DOXORUBICINHYDROCHLORIDE	>240
5-FLUOROURACIL	>240
METHOTREXATE	>240
ETOPOSIDE	>240
PACLITAXEL	<10
THIOTEPA	30 (28,30,33)

Results achieved under controlled laboratory conditions, by accredited external testing laboratory. *For Bioclean D and Bioclean 2000, the chemical permeation results relates to the fabric performance for reference only. Seams and closures may have lower breakthrough times. We recommend garments with sealed seams such as Bioclean-C to be worn over the coverall for added protection against chemotherapy drugs handling.

SIZE CHART

S-BDSH-XS; Size: XS, Chest: 76-84cm (30"-33"), Height: 158-164cm (5'2"-5'4") S-BDSH-S; Size: S, Chest: 84-92cm (33"-36"), Height: 164-170cm (5'4"-5'6") S-BDSH-M; Size: M, Chest: 92-100cm (36"-39"), Height: 170-176cm (5'6"-5'9") S-BDSH-L; Size: L, Chest: 100-108cm (39"-42"), Height: 176-182cm (5'9"-6'0") S-BDSH-XL; Size: XL, Chest: 108-116cm (42"-45"), Height: 182-188cm (6'0"-6'2) S-BDSH-2XL; Size: 2XL, Chest: 116-124cm (45"-48"), Height: 188-194cm (6'2"-6'4") S-BDSH-3XL; Size: 3XL, Chest: 124-132cm (48"-51"), Height: 194-200cm (6'4"-6'6") S-BDSH-4XL; Size: 4XL, Chest: 132-140cm (51"-54"), Height: 200-206cm (6'6"-6'8") S-BDSH-5XL; Size: 5XL, Chest: 140-148cm (54"-56"), Height: 212-218cm (6'11"7'2") S-BDSH-6XL; Size: 6XL, Chest: 148-156cm (56"-58"), Height: 212-218cm (6'11"-7'2") S-BDSH-7XL; Size: 7XL, Chest: 156-164cm (61"-64"), Height: 224-230cm (7'4"-7'6")





BioClean-D™ Dropdown Sterile Coverall with Hood S-BDSH

MATERIAL PERFORMANCE TEST RESULTS

TEST	RESULT	PERFORMANCE CLASS	PERFORMANCE STANDARD
Abrasion Resistance	>10 cycles	1	EN 12947-2
Flex Cracking Resistance	>50,000 cycles	6	EN ISO 7854
Puncture Resistance	>5 N	1	ISO 13996
Trapezoidal Tear Resistance Cross Direction (CD)	>10 N	1	EN ISO 9073-4
Trapezoidal Tear Resistance Machine Direction (MD)	>10 N	1	EN ISO 9073-4
Tensile Strength Cross Direction (CD)	>30 N	1	EN ISO 13934-1
Tensile Strength Machine Direction (MD)	>30 N	1	EN ISO 13934-1
Repellence to Liquids - 30% H ₂ SO ₄	>90%	3	ISO 6530
Repellence to Liquids - 10% NaOH	>90%	3	ISO 6530
Repellence to Liquids - O-Xylene	>90%	3	ISO 6530
Repellence to Liquids - Butan-1-ol	>90%	3	ISO 6530
Penetration by Liquids - 30% H ₂ SO ₄	<1%	3	ISO 6530
Penetration by Liquids - 10% NaOH	<1%	3	ISO 6530
Penetration by Liquids - O-Xylene	<1%	3	ISO 6530
Penetration by Liquids - Butan-1-ol	<1%	3	ISO 6530
Seam Strength ²	>50 N	2	ISO 13935-2
Electrostatic Charge Half Decay Time, t ₅₀ (secs)	PASS	N/A	EN1149-3

^{1.} Seam not destroyed

ORDERING INFORMATION

	SIZE	XS, S, M, L, XL, 2XL	3XL, 4XL, 5XL, 6XL, 7XL, 8XL
S-BDSH	REORDER NO.	S-BDSH-XS, S-BDSH-S, S- BDSH-M, S-BDSH-L, S-BDSH- XL, S-BDSH-2XL	S-BDSH-3XL, S-BDSH-4XL, S- BDSH-5XL, S-BDSH-6XL, S- BDSH-7XL, S-BDSH-8XL

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

 Latin America & Caribbean Region
 Ansell Nitritex

 Ansell Commercial Mexico S.A. de C.V.
 T: +44 1638 663338

 T: +52 442 248 1544 / 248 3133
 F: +44 1638 668890

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Regulatory Compliance

Performance Standards and

Ansell, $^{\textcircled{R}}$ and $^{\textcircled{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{M}}$ 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

Please see product validation pack or contact Ansell customer service for specific data on use of garments with cytotoxic drugs Garments used for protection against such drugs must be selected specifically for the type of chemicals used.



^{2.} The material is static dissipative. 3. Tested in accordance with EN1149-5