

# Cobalt® X N21

**Fully Textured Nitrile Exam Glove** 

# Strong nitrile gloves with extra thickness for additional protection

- Tear-resistant: MICROFLEX<sup>®</sup> Cobalt<sup>®</sup> X N21 disposable gloves feature an extrathick nitrile design — 5 mil thick at the palm, these strong, blue nitrile gloves resist tearing even during the toughest iobs
- Secure grip: Excellent for active jobs which require workers to firmly grip tools, equipment and other objects, these gloves are fully textured to prevent accidental drops
- Food handling compliance: These latexfree exam gloves are suitable for a wide range of food-handling applications, particularly for food processing workers in contact with rough edges like bones or frozen foods
- Medical exam grade: These gloves are also medical exam grade, and can be used by doctors, nurses, physician's assistants and other healthcare or dental professionals in need of sturdy, durable exam gloves for jobs like equipment cleaning or office disinfection



### **Industries**

- Food Processing
- Life Sciences
- Healthcare

### **Recommended For**

- Equipment, maintenance and repair
- All food processing, applications that have food contact
- Assembly of parts
- Sample taking and processing
- Standard, moderate risk examination procedures
- Protection from Type I latex allergy in HCW's or patients



# **TECHNICAL DATA SHEET**

	Product Information
External Glove Surface	Fully Textured
Audit Standards	EN ISO 13485:2012
<b>Product Certification</b>	ASTM D6319, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
<b>Product Segmentation</b>	Robust
Antistatic	Not Tested
Silicone Free	No

# **PHYSICAL PROPERTIES**

	Typical	Typical Values	
Length (mm/inches)	240 ,	240 / 9.5	
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12 ,	0.12 / 4.7	
Finger Thickness (mm/mils)	0.14	0.14 / 5.5	
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	23	22	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412

# **ORDERING INFORMATION**

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	N211	N212	N213	N214

# For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.cor JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

**Latin America & Caribbean Region** BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell,  $^{\textcircled{8}}$  and  $^{\textcircled{M}}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\textcircled{9}}$  2025 Ansell Limited. All Rights Reserved.

