

## Latex exam gloves, offering robust personal protection and secure grip

- **Durable latex:** Soft, stretchable latex provides tough chemical splash protection and superior comfort
- **Secure grip:** These latex medical exam gloves have been developed with textured fingertips for a confident grip even when handling slippery, oily objects
- **Enhanced finger thickness:** 0.20 mm/7.9 mil finger thickness results in greater protection from snags, tears and rips when compared with standard latex alternatives
- **Elevated comfort:** An extra wash during manufacturing makes these gloves smooth, comfortable and are easy to don



**CAUTION:** This product contains natural rubber latex, which may cause allergic reactions

### Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Healthcare
- Fire and Rescue

### Recommended For

- General Purpose Auto Aftermarket
- Tire rotation & changes
- Sample taking and processing
- Raw material sample collection
- Standard, moderate risk examination procedures
- Oil, fluids and filter change
- Maintaining lab furniture and equipment
- Inspection (picking, checking and marking)
- Inspection, selecting, checking parts
- Engine transmission and repair

## TECHNICAL DATA SHEET

Product Information	
<b>Material</b>	Natural Rubber Latex
<b>External Glove Surface</b>	Textured Fingers
<b>Audit Standards</b>	EN ISO 13485:2012
<b>Product Certification</b>	ASTM D3578, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade
<b>Packaging Overview</b>	100 gloves per dispenser 10 dispensers per case 1000 gloves per case 90 gloves per dispenser 10 dispensers per case 900 gloves per case (size XXL)
<b>Storage Instructions</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country Of Origin</b>	Malaysia
<b>Product Segmentation</b>	Robust
<b>Antistatic</b>	Not Tested
<b>Silicone Free</b>	No

## PHYSICAL PROPERTIES

	Typical Values		Testing Method
	BEFORE AGING	AFTER AGING	
Length (mm/inches)	245 / 9.65		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.16/6.3		ASTM D5151,EN 455-2
Finger Thickness (mm/mils)	0.21/8.3		ASTM D5151,EN 455-2
Ultimate Tensile Strength (MPa)	21	18	ASTM D412 & D573
Elongation at Break (%)	≥ 750	≥ 600	ASTM D412
Force at break (N)	≥ 16	≥ 6	EN 455-2

## ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	MF-300-XS	MF-300-S	MF-300-M	MF-300-L	MF-300-XL	MF-300-XXL

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV

T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### Asia Pacific Region

MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

#### North America Region

Ansell Healthcare Products LLC

T: +1 800 800 0444  
F: +1 800 800 0445

#### Latin America & Caribbean Region

BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

#### Australia

Ansell Limited

T: +61 1800 337 041  
F: +61 1800 803 578

#### Russia

Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

